



**OPPA European Social Fund
Prague & EU: We invest in your future.**

AE4M33RZN, Fuzzy logic: Fuzzy description logic

Radomír Černoč

radomir.cernoch@fel.cvut.cz

Faculty of Electrical Engineering, CTU in Prague

3/12/2012

Crisp description logic

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H} = role hierarchies
- I = inverse properties
- \mathcal{F}
 - concept intersection
 - universal restrictions
 - limited existential quantification
 - role restriction
- \mathcal{D} = data types

SHIF concepts

Let A and R be the sets of *atomic concepts* and *atomic roles*.

Concept constructors

$C, D := \top \mid \perp$	top and bottom concepts	(1)
$\mid A$	atomic concept	(2)
$\mid \neg C$	concept negation	(3)
$\mid C \sqcap D$	intersection	(4)
$\mid C \sqcup D$	concept union	(5)
$\mid \forall R \cdot C$	full universal quantification	(6)
$\mid \exists R \cdot C$	full existential quantification	(7)

Crisp description logic ontology

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$. We use the set of individuals I :

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \rangle$
and *role assertions* $\langle (i, j \in I) : r \in R \rangle$.

$\mathcal{T}Box$ (Terminology Box)

Contains *general concept inclusion* (GCI) axioms $\langle C \sqsubseteq D \rangle$ and role axioms (role hierarchy $\langle R_1 \sqsubseteq R_2 \rangle$, transitivity, ...).

Crisp description logic interpretation

Interpretation \mathcal{I} is a tuple $(\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$ (*interpretation domain*, *interpretation function*), which maps

an individual to domain object

$$i^{\mathcal{I}} \in \Delta^{\mathcal{I}}$$

an atomic concept to domain subsets

$$C^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$$

an atomic role to subset of domain tuples

$$R^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$$

Crisp description logic interpretation

The non-atomic concepts are interpreted as follows:

non-atomic concept	its interpretation
\top	$\Delta^{\mathcal{I}}$
\perp	\emptyset
$\neg C$	$\Delta^{\mathcal{I}} \setminus C^{\mathcal{I}}$
$C \sqcap D$	$C^{\mathcal{I}} \cap D^{\mathcal{I}}$
$C \sqcup D$	$C^{\mathcal{I}} \cup D^{\mathcal{I}}$
$\forall R \cdot C$	$\{x \mid \forall y \in \Delta^{\mathcal{I}}. ((x, y) \in R^{\mathcal{I}}) \Rightarrow (y \in C^{\mathcal{I}})\}$
$\exists R \cdot C$	$\{x \mid \exists y \in \Delta^{\mathcal{I}}. ((x, y) \in R^{\mathcal{I}}) \wedge (y \in C^{\mathcal{I}})\}$

Crisp notion of truth

Axiom satisfaction

axiom	satisfied when
$\langle i : C \rangle$	$i^{\mathcal{I}} \in C^{\mathcal{I}}$
$\langle (i, j) : R \rangle$	$(i^{\mathcal{I}}, j^{\mathcal{I}}) \in R^{\mathcal{I}}$
$\langle C \sqsubseteq D \rangle$	$C^{\mathcal{I}} \sqsubseteq D^{\mathcal{I}}$
transitive(R)	$R^{\mathcal{I}}$ is transitive
...	

- Concept C is *satisfiable* iff there is an interpretation \mathcal{I} s.t. $\mathcal{I} \models \langle i : C \rangle$ for some i .
- Interpretation \mathcal{I} *satisfies* a knowledgebase $\mathcal{K} = \mathcal{A}Box + \mathcal{T}Box$ (or \mathcal{I} is a *model* of \mathcal{K}) iff \mathcal{I} satisfies all its axioms.
- Axiom T is a *logical consequence* of \mathcal{K} iff every model of \mathcal{K} satisfies T . We write $\mathcal{K} \models T$.

Fuzzy description logic

Basic idea

1. Keep the the previous slides intact.
2. Add \circ below and above every operation.
3. Watch the semantic change.

Overview

We will show the **fuzzyDL** reasoner [Bobillo and Straccia, 2008] capabilities, which extends the $\mathcal{SHIF}(\mathcal{D})$ family with fuzzy capabilities.

Concept constructors

We start with atomic concepts A . Derived concepts are on the next slide together with their interpretation. (Each concept is interpreted as a fuzzy subset of the domain.)

Fuzzy DL interpretation

Fuzzy interpretation \mathcal{I} is a tuple $\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}}$ which maps

an individual to a domain object

$$i^{\mathcal{I}} \in \Delta^{\mathcal{I}}$$

an atomic concept to a domain subsets

$$C^{\mathcal{I}} \in \mathbb{F}(\Delta^{\mathcal{I}})$$

an atomic role to a relation on the domain

$$R^{\mathcal{I}} \in \mathbb{F}(\Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}})$$

$C, D :=$	interpretation of x
\perp	$\mathbf{0}$
\top	$\mathbf{1}$
A	$A^{\mathcal{F}}(x)$
$\neg C$	$\neg_S C^{\mathcal{F}}(x)$
$C \underset{S}{\sqcap} D$	$C^{\mathcal{F}}(x) \underset{S}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{L}{\sqcap} D$	$C^{\mathcal{F}}(x) \underset{L}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{S}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{S}{\vee} D^{\mathcal{F}}(x)$
$C \underset{L}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{L}{\vee} D^{\mathcal{F}}(x)$
$C \underset{S}{\overset{R}{\rightrightarrows}} D$	$C^{\mathcal{F}}(x) \underset{S}{\overset{R}{\rightrightarrows}} D^{\mathcal{F}}(x)$
$C \underset{L}{\overset{R}{\rightrightarrows}} D$	$C^{\mathcal{F}}(x) \underset{L}{\overset{R}{\rightrightarrows}} D^{\mathcal{F}}(x)$
$C \underset{S}{\overset{S}{\rightrightarrows}} D$	$C^{\mathcal{F}}(x) \underset{S}{\overset{S}{\rightrightarrows}} D^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
$\exists R \cdot C$	$\sup_y R^{\mathcal{F}}(x, y) \overset{\circ}{\wedge} C^{\mathcal{F}}(y)$
$\forall R \cdot C$	$\inf_y R^{\mathcal{F}}(x, y) \overset{\circ}{\Rightarrow} C^{\mathcal{F}}(y)$
$(n C)$	$n \cdot C(x)$
$\text{mod}(C)$	$\text{mod}(C^{\mathcal{F}}(x))$
$w_1 C_1 + \dots + w_k C_k$	$w_1 C_1^{\mathcal{F}}(x) + \dots + w_k C_k^{\mathcal{F}}(x)$
$C \overset{\circ}{\leq} n$	$\begin{cases} C^{\mathcal{F}}(x) & C^{\mathcal{F}}(x) \overset{\circ}{\leq} n \\ 0 & \text{otherwise} \end{cases}$

Male \square Female \neq \perp



Modifiers

Modifier is a function that alters the membership function.

Example

Linear modifier of degree c is

$$a = \frac{c}{c + 1}$$

$$b = \frac{1}{c + 1}$$

Fuzzy DL ontology

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$:

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \mid \alpha \rangle$ and *role assertions* $\langle (i, j \in I) : r \in R \mid \alpha \rangle$.

$\mathcal{T}Box$ (Terminology Box)

GCI axioms $\langle C \sqsubseteq D \mid \alpha \rangle$ state that “C is D at least by α ”.

Besides GCI, there are role hierarchy axioms $\langle R_1 \sqsubseteq R_2 \rangle$, transitivity axioms and definitions of inverse relations.

Notion of a fuzzy truth

Fuzzy axioms

axiom	satisfied if
$\langle i : C \mid \alpha \rangle$	$C^{\mathcal{F}}(i^{\mathcal{F}}) \geq \alpha$
$\langle (i, j) : R \mid \alpha \rangle$	$R^{\mathcal{F}}(i^{\mathcal{F}}, j^{\mathcal{F}}) \geq \alpha$
$\langle C \sqsubseteq D \mid \alpha \rangle$	$C \stackrel{\circ}{\subseteq} D \geq \alpha$
$\langle R_1 \sqsubseteq R_2 \rangle$	$R_1^{\mathcal{F}} \subseteq R_2^{\mathcal{F}}$
$\langle \text{transitive } R \rangle$	R is \circ -transitive
$\langle R_1 = R_2^{-1} \rangle$	$R_1^{\mathcal{F}} = (R_2^{\mathcal{F}})^{-1}$

Using these definitions, the notions of *logical consequence* and *satisfiability* (of both concepts and axioms) remains the same. More on slide 307.

What can you ask the reasoner?

Best/Worst Degree Bound

What is the minimal degree of an axiom that \mathcal{K} ensures?

$$bdb(\mathcal{K}, \tau) = \sup\{\alpha \mid \mathcal{K} \models \langle \tau \mid \alpha \rangle\}$$

$$wdb(\mathcal{K}, \tau) = \inf\{\alpha \mid \mathcal{K} \models \langle \tau \mid \alpha \rangle\}$$

where τ is an axiom of type $\langle i : C \rangle$ or $\langle (i, j) : R \rangle$ or $\langle C \sqsubseteq D \rangle$.

- From an empty \mathcal{K} , you cannot infer anything and therefore $bdb(\mathcal{K}, \tau) = 1$ and $wdb(\mathcal{K}, \tau) = 0$ (if using atomic concepts only). Only by adding new axioms into \mathcal{K} , the bounds “tighten up”.
- What happens if $wdb(\mathcal{K}, \tau) \geq bdb(\mathcal{K}, \tau)$ for some axiom τ ?

What can you ask the reasoner?

Best Satisfiability Bound

What is the maximal degree of satisfiability of C ?

$$bsb(\mathcal{K}, C) = \sup_{\mathcal{I}} \sup_{x \in \Delta} \{C^{\mathcal{I}}(x) \mid \mathcal{I} \models \mathcal{K}\}.$$

This is a generalization of *concept satisfiability*.

Bibliography



Baader, F. (2003).

The Description Logic Handbook: Theory, Implementation, and Applications.

Cambridge University Press.



Bobillo, O. and Straccia, U. (2008).

fuzzydl: An expressive fuzzy description logic reasoner.

In In Proc. FUZZ-IEEE-2008. IEEE Computer Society, pages 923--930.



**OPPA European Social Fund
Prague & EU: We invest in your future.**
