

Input/Output and Standard C Library

Jan Faigl

Department of Computer Science
Faculty of Electrical Engineering
Czech Technical University in Prague

Lecture 06

B3B36PRG – C Programming Language



Overview of the Lecture

- Part 1 – Input and Output

- File Operations

- Character Oriented I/O

- Text Files

- Block Oriented I/O

- Non-Blocking I/O

- Terminal I/O

K. N. King: chapters 22

- Part 2 – Selected Standard Libraries

- Standard library – Selected Functions

- Error Handling

K. N. King: chapters 21, 23, 24, 26, and 27



Part I

Input and Output



Text vs Binary Files

- There is no significant difference between text and binary files from the machine processing perspective
- Text files are oriented to be a human readable
 - In text files, bytes represent characters
 - The content is usually organized into lines
 - Different markers for the *end-of-line* are used (1 or 2 bytes)
 - There can be a special marker for the *end-of-file* (Ctrl-Z)
It is from CP/M and later used in DOS. It is not widely used in Unix like systems.
 - For parsing text files, we can use
 - Character oriented functions – `putchar()`, `getchar()`, `putc()`, `getc()`
 - Functions for formatted i/o – `printf()` and `scanf()` as shortcuts for the `fprintf()` and `fscanf()` with the `stdin` and `stdout` streams
 - Line oriented functions – `puts()`, `gets()` and variants `fputs()`, `fgets()`
- Text files can be considered as a sequence of bytes
 - Numeric values as text need to be parsed and formatted in writing
- Numbers in binary files may deal with byte ordering

E.g., ARM vs x86



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



File open

- Functions for input/output are defined in the standard library `<stdio.h>`
- The file access is through using a pointer to a file (stream) `FILE*`
- File can be opened using `fopen()`

```
FILE* fopen(const char * restrict path, const char * restrict mode);
```

- Operations with the files are
 - Stream oriented – sequential reading/writing
 - The `current position in the file is like a cursor`
 - At the opening the file, the cursor is set to the beginning of the file
- The mode of the file operations is specified in the `mode` parameter
 - `"r"` – reading from the file

Notice, the restrict keyword

The program (user) needs to have sufficient rights for reading from the file.

- `"w"` – writing to the file

A new file is created if it does not exists; otherwise the content of the file is cleared.

- `"a"` – append to the file – the cursor is set to the end of the file
- The modes can be combined, e.g., `"r+"` open the file for reading and writing



fopen(), fclose(), and feof()

- Test if the file has been opened

```
1 char *fname = "file.txt";
2
3 if ((f = fopen(fname, "r")) == NULL) {
4     fprintf(stderr, "Error: open file '%s'\n", fname);
5 }
```

- Close file – `int fclose(FILE *stream);`

```
1 if (fclose(f) == EOF) {
2     fprintf(stderr, "Error: close file '%s'\n", fname);
3 }
```

- Test of reaching the end-of-file (EOF) – `int feof(FILE *stream);`



File Positioning

- Every stream has a cursor, i.e., an associated file position
- The position can be set using `offset` relatively to `whence`
- `int fseek(FILE *stream, long offset, int whence);`
where `whence`
 - `SEEK_SET` – set the position from the beginning of file
 - `SEEK_CUR` – relatively to the current file position
 - `SEEK_END` – relatively to the end of file

If the position is successfully set, `fseek()` returns 0

- `void rewind(FILE *stream);` sets the position to the beginning of file
- The position can be stored and set by the functions

```
int fgetpos(FILE * restrict stream, fpos_t * restrict pos);  
int fsetpos(FILE *stream, const fpos_t *pos);
```

See `man fseek`, `man rewind`, etc



File Stream Modes

- Modes in the `fopen()` can be combined

```
FILE* fopen(const char * restrict path, const char * restrict mode);
```

- "r" open for reading
 - "w" Open for writing (file is created if it does not exist)
 - "a" open for appending (set cursor to the end of file or create a new file if it does not exist)
 - "r+" open for reading and writing (starts at beginning)
 - "w+" open for reading and writing (truncate if file exists)
 - "a+" open for reading and writing (append if file exists)
- There are restrictions for the combined modes with "+"
 - We cannot switch from reading to writing without calling a file-positioning function or reaching the end of file
 - We cannot switch from writing to reading without calling `fflush()` or calling a file-positioning function.



Temporary Files

- `FILE* tmpfile(void);` – creates a temporary file that exists until it is closed or the program exists
- `char* tmpnam(char *s);` – generates a name for a temporary file
 - If `s` is `NULL`, it creates a name and store it in a static variable and return a pointer to it
 - Otherwise it copies the string into the provided character array (`s`) and returns the pointer to the first character of the array



File Buffering

- `int fflush(FILE *stream);` – flushes buffer for the given `stream`
 - `fflush(NULL);` – flushes all buffers (all output streams)

- Change the buffering mode, size, and location of the buffer

```
int setvbuf(FILE * restrict stream, char * restrict buf, int mode, size_t  
size);
```

The `mode` can be one of the following macros

`_IOFBF` – full buffering. Data are read from the stream when buffer is empty and written to the stream when it is full

`_IOLBF` – line buffering. Data are read or written from/to the stream one line at a time

`_IONBF` – no buffer. Direct reading and writing without buffer

```
#define BUFFER_SIZE 512  
char buffer[BUFFER_SIZE];  
  
setvbuf(stream, buffer, _IOFBF, BUFFER_SIZE);
```

- `void setbuf(FILE * restrict stream, char * restrict buf);`
 - similar to `setvbuf()` but with default mode



Detecting End-of-File and Error Conditions

- Three possible “errors” can occur during reading data (e.g., `fscanf`)
 - **End-of-file** – we reach the end of file
 - Or, the stream is closed, e.g., `stdin`*
 - **Read error** – the read function is unable to read data from the stream
 - **Matching failure** – the read data does not match the requested format
- Each stream (`FILE*`) has two indicators:
 - **error indicator** – indicates that a read or write error occurs
 - **end-of-file indicator** – is set when the end of file is reached
- The indicators can be read (tested if the indicator is set or not) and clear the error and eof indicators
 - `int ferror(FILE *stream);`
 - `void clearerr(FILE *stream);`
 - `int feof(FILE *stream);`



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



Reading and Writing Single Byte

- Basic function for reading from `stdin` and `stdout` are
 - `getchar()` and `putchar()`
 - Both function return `int` value, to indicate an error (`EOF`)
 - The written and read values are converted to `unsigned char`
- The variants of the function for the specific stream are
 - `int getc(FILE *stream);` and
`int putc(int c, FILE *stream);`
 - `getchar()` is equivalent to `getc(stdin)`
 - `putchar()` is equivalent to `putc()` with the `stdout` stream
- Reading byte-by-byte (`unsigned char`) can be also used to read binary data, e.g., to construct 4 bytes length `int` from the four byte (`char`) values



Example – Copy using getc() and putc() 1/2

- Simple copy program based on reading bytes from `stdin` and writing them to `stdout`

```
1 int c;
2 int bytes = 0;
3 while ((c = getc(stdin)) != EOF) {
4     if (putc(c, stdout) == EOF) {
5         fprintf(stderr, "Error in putc");
6         break;
7     }
8     bytes += 1;
9 }
```

lec06/copy-getc_putc.c



Example – Copy using getc() and putc() 2/2

- We can count the number of bytes, and thus the time needed to copy the file

```
1 #include <sys/time.h>
2 ...
3
4 struct timeval t1, t2;
5 gettimeofday(&t1, NULL);
6
7 ... // copy the stdin -> stdout
8
9 gettimeofday(&t2, NULL);
10 double dt = t2.tv_sec - t1.tv_sec + ((t2.tv_usec - t1.tv_usec) / 1000000.0);
11 double mb = bytes / (1024 * 1024);
12 fprintf(stderr, "%.2lf MB/sec\n", mb / dt);
```

lec06/copy-getc_putc.c

- Example of creating random file and using the program

```
clang -O2 copy-getc_putc.c
dd bs=512m count=1 if=/dev/random of=/tmp/rand1.dat
1+0 records in
1+0 records out
536870912 bytes transferred in 7.897227 secs (67982205 bytes/sec)
./a.out < /tmp/rand1.dat >/tmp/rand2.dat
326.10 MB/sec
```



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



Line Oriented I/O

- A whole line (text) can be read by

```
char* gets(char *str);  
char* fgets(char * restrict str, int size, FILE * restrict stream);
```

- `gets()` cannot be used securely due to lack of bounds checking
- A line can be written by `fputs()` and `puts()`
- `puts()` writes the given string and a newline character to the `stdout` stream
- `puts()` and `fputs()` return a non-negative integer on success and `EOF` on error

See `man fgets`, `man fputs`

- Alternatively, the line can be read by `getline()`

```
ssize_t getline(char ** restrict linep, size_t * restrict linecapp,  
FILE * restrict stream);
```

Expand the buffer via `realloc()`, see `man getline`

*Capacity of the buffer, or if `*linep==NULL` (if `linep` points to `NULL`) a new buffer is allocated*



Formatted I/O – fscanf()

- `int fscanf(FILE *file, const char *format, ...);`

- It returns a number of read items, e.g., for the input

record 1 13.4

- The statement `int r = fscanf(f, "%s %d %lf\n", str, &i, &d);`

- sets (in the case of success) the variable `r` to the value 3

`r == 3`

- For reading strings, it is necessary to respect the size of the allocated memory, e.g., by using the limited length of the read string

```
char str[10];  
int r = fscanf(f, "%9s %d %lf\n", str, &i, &d);
```

lec06/file_scanf.c



Formatted I/O – fprintf()

- `int fprintf(FILE *file, const *format, ...);`

```
int main(int argc, char *argv[])
{
    char *fname = argc > 1 ? argv[1] : "out.txt";
    FILE *f;
    if ((f = fopen(fname, "w")) == NULL) {
        fprintf(stderr, "Error: Open file '%s'\n", fname);
        return -1;
    }
    fprintf(f, "Program arguments argc: %d\n", argc);
    for (int i = 0; i < argc; ++i) {
        fprintf(f, "argv[%d]='%s'\n", i, argv[i]);
    }
    if (fclose(f) == EOF) {
        fprintf(stderr, "Error: Close file '%s'\n", fname);
        return -1;
    }
    return 0;
}
```

lec06/file_printf.c



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



Block Read/Write

- We can use `fread()` and `fwrite()` to read/write a block of data

```
size_t fread(void * restrict ptr,  
           size_t size, size_t nmemb,  
           FILE * restrict stream);
```

```
size_t fwrite(const void * restrict ptr,  
             size_t size, size_t nmemb,  
             FILE * restrict stream);
```

Use `const` to indicate (`ptr`) is used only for reading



Block Read/Write – Example 1/5

- Program to read/write a given (as `#define NUMB`) number of `int` values using `#define BUFSIZE` length buffer
- Writing is enabled by the optional program argument `-w`
- File for reading/writing is a mandatory program argument

```
1 #include <stdio.h>
2 #include <string.h>
3 #include <errno.h>
4 #include <stdbool.h>
5 #include <stdlib.h>
6
7 #include <sys/time.h>
8
9 #include "my_assert.h"
10
11 #ifndef BUFSIZE
12 #define BUFSIZE 32768
13 #endif
14
15 #ifndef NUMB
16 #define NUMB 4098
17 #endif
```

```
19 int main(int argc, char *argv[])
20 {
21     int c = 0;
22     _Bool read = true;
23     const char *fname = NULL;
24     FILE *file;
25     const char *mode = "r";
26     while (argc-- > 1) {
27         fprintf(stderr, "DEBUG: argc: %d '%s'\n", argc, argv[argc]);
28         if (strcmp(argv[argc], "-w") == 0) {
29             fprintf(stderr, "DEBUG: enable writting\n");
30             read = false; // enable writting
31             mode = "w";
32         } else {
33             fname = argv[argc];
34         }
35     } // end while
```

lec06/demo-block_io.c



Block Read/Write – Example 2/5

```
36 file = fopen(fname, mode);
37 if (!file) {
38     fprintf(stderr, "ERROR: Cannot open file '%s', error %d - %s\n", fname, errno,
39             strerror(errno));
40     return -1;
41 }
42 int *data = (int*)malloc(NUMB * sizeof(int));
43 my_assert(data __LINE__, __FILE__);
44 struct timeval t1, t2;
45 gettimeofday(&t1, NULL);
46 if (read) {                                     /* READ FILE */
47     fprintf(stderr, "INFO: Read from the file '%s'\n", fname);
48     c = fread(data, sizeof(int), NUMB, file);
49     if (c != NUMB) {
50         fprintf(stderr, "WARN: Read only %i objects (int)\n", c);
51     } else {
52         fprintf(stderr, "DEBUG: Read %i objects (int)\n", c);
53     }
54 } else {                                         /* WRITE FILE */
55     char buffer[BUFSIZE];
56     if (setvbuf(file, buffer, _IOFBF, BUFSIZE)) { /* SET BUFFER */
57         fprintf(stderr, "WARN: Cannot set buffer");
58     }
59 }
```

lec06/demo-block_io.c



Block Read/Write – Example 3/5

```
58     fprintf(stderr, "INFO: Write to the file '%s'\n", fname);
59     c = fwrite(data, sizeof(int), NUMB, file);
60     if (c != NUMB) {
61         fprintf(stderr, "WARN: Write only %i objects (int)\n", c);
62     } else {
63         fprintf(stderr, "DEBUG: Write %i objects (int)\n", c);
64     }
65     fflush(file);
66 }
67
68 gettimeofday(&t2, NULL);
69 double dt = t2.tv_sec - t1.tv_sec + ((t2.tv_usec - t1.tv_usec) / 1000000.0);
70 double mb = (sizeof(int) * c) / (1024 * 1024);
71 fprintf(stderr, "DEBUG: feof: %i ferror: %i\n", feof(file), ferror(file));
72 fprintf(stderr, "INFO: %s %lu MB\n", (read ? "read" : "write"), sizeof(int)*NUMB/(1024 *
    1024));
73 fprintf(stderr, "INFO: %.2lf MB/sec\n", mb / dt);
74 free(data);
75 return EXIT_SUCCESS;
76 }
```



Block Read/Write – Example 3/5

- Default `BUFSIZE` (32 kB) to write/read 10^8 integer values (~ 480 MB)

```
clang -DNUMB=100000000 demo-block_io.c && ./a.out -w a 2>&1 | grep INFO
INFO: Write to the file 'a'
INFO: write 381 MB
INFO: 10.78 MB/sec

./a.out a 2>&1 | grep INFO
INFO: Read from the file 'a'
INFO: read 381 MB
INFO: 2214.03 MB/sec
```

- Try to read more elements results in `feof()`, but not in `ferror()`

```
clang -DNUMB=200000000 demo-block_io.c && ./a.out a
DEBUG: argc: 1 'a'
INFO: Read from the file 'a'
WARN: Read only 100000000 objects (int)

DEBUG: feof: 1 ferror: 0

INFO: read 762 MB
INFO: 1623.18 MB/sec
```

lec06/demo-block_io.c



Block Read/Write – Example 5/5

- Increased write buffer `BUFSIZE` (128 MB) improves writing performance

```
clang -DNUMB=100000000 -DBUFSIZE=134217728 demo-block_io.c && ./a.out -w aa 2>&1 | grep INFO
INFO: Write to the file 'aa'
INFO: write 381 MB
INFO: 325.51 MB/sec
```

- But does not improve reading performance, which relies on the standard size of the buffer

```
clang -DNUMB=100000000 -DBUFSIZE=134217728 demo-block_io.c && ./a.out aa 2>&1 | grep INFO
INFO: Read from the file 'aa'
INFO: read 381 MB
INFO: 1693.39 MB/sec
```

lec06/demo-block_io.c



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



Blocking and Non-Blocking I/O Operations

- Usually I/O operations are considered as **blocking requested**
 - System call does not return control to the application until the requested I/O is completed
 - It is motivated that we need all the requested data and I/O operations are usually slower than the other parts of the program.
- We have to wait for the data anyway*
- It is also called **synchronous** programming
- **Non-Blocking** system calls do not wait for unrelated I/O to complete, and thus do not block the application
 - It is suitable for network programming, multiple clients, graphical user interface, or when we need to avoid “deadlock” or too long waiting due to slow or not reliable communication
 - Call for reading requested data will read (and “return”) only data that are actually available in the input buffer
- **Asynchronous** programming with **non-blocking** calls
 - Return control to the application immediately
 - Data are transferred to/from buffer “on the background” *Call back, triggering a signal, etc.*



Non-Blocking I/O Operations – Example

- Setting the file stream (file descriptor) to the `O_NONBLOCK` mode

Also for socket descriptor

- For reading from regular files it does not make too much sense to use non-blocking operations
- Reading from block devices such as serial port, e.g., `/dev/ttyS10` may be more suitable
 - We can set `O_NONBLOCK` flag for a file descriptor using `fcntl()`

```
#include <fcntl.h> // POSIX

// open file by the open() system call that return a file descriptor
int fd = open("/dev/ttyUSB0", O_RDWR, S_IRUSR | S_IWUSR);

// read the current settings first
int flags = fcntl(fd, F_GETFL, 0);

// then, set the O_NONBLOCK flag
fcntl(fd, F_SETFL, flags | O_NONBLOCK);
```

- Then, calling `read()` will provide the requested number of bytes are fewer bytes than are currently available in the buffer



Outline

File Operations

Character Oriented I/O

Text Files

Block Oriented I/O

Non-Blocking I/O

Terminal I/O



Key Press without Enter

- Reading character from `stdin` can be made by the `getchar()` function
- However, the input is buffered to read line, i.e., it is necessary to press Enter key by default
- We can avoid that by setting the terminal to a `raw` mode

```
#include <stdio.h>
#include <ctype.h>

int c;
while ((c = getchar()) != 'q') {
    if (isalpha(c)) {
        printf("Key '%c' is alphabetic;", c);
    } else if (isspace(c)) {
        printf("Key '%c' is space character;", c);
    } else if (isdigit(c)) {
        printf("Key '%c' is decimal digit;", c);
    } else if (isblank(c)) {
        printf("Key is blank;");
    } else {
        printf("Key is something else;");
    }
    printf(" ascii: %s\n",
           isascii(c) ? "true" : "false");
}
return 0;
```

lec06/demo-getchar.c



Key Press without Enter – Example

- We can switch the `stdin` to the `raw` mode using `termios`

```
void call_termios(int reset)
{
    static struct termios tio, tioOld;
    tcgetattr(STDIN_FILENO, &tio);
    if (reset) {
        tcsetattr(STDIN_FILENO, TCSANOW, &tioOld);
    } else {
        tioOld = tio; //backup
        cfmakeraw(&tio);
        tio.c_lflag &= ~ECHO; // assure echo is disabled
        tio.c_oflag |= OPOST; // enable output postprocessing
        tcsetattr(STDIN_FILENO, TCSANOW, &tio);
    }
}
```

- Or we can use the `stty` tool

```
void call_stty(int reset)
{
    if (reset) {
        system("stty -raw opost echo");
    } else {
        system("stty raw opost -echo");
    }
}
```

- Usage `clang demo-getchar.c -o demo-getchar`

- Standard "Enter" mode: `./demo-getchar`
- Raw mode - `termios`: `./demo-getchar termios`
- Raw mode - `stty`: `./demo-getchar stty`

`lec06/demo-getchar.c`



Part II

Selected Standard Libraries



Outline

Standard library – Selected Functions

Error Handling



Standard Library

- The C programming language itself does not provide operations for input/output, more complex mathematical operations, nor:
 - string operations
 - dynamic allocation
 - run-time error handling
- These and further functions are included in the standard library that is a part of the C compiler
 - Library – the compiled code is linked to the program, e.g., `libc.so`

Viz e.g., `ldd a.out`

- Header files contain function prototypes, types , macros, etc.

<code><assert.h></code>	<code><inttypes.h></code>	<code><signal.h></code>	<code><stdlib.h></code>
<code><complex.h></code>	<code><iso646.h></code>	<code><stdarg.h></code>	<code><string.h></code>
<code><ctype.h></code>	<code><limits.h></code>	<code><stdbool.h></code>	<code><tgmath.h></code>
<code><errno.h></code>	<code><locale.h></code>	<code><stddef.h></code>	<code><time.h></code>
<code><fenv.h></code>	<code><math.h></code>	<code><stdint.h></code>	<code><wchar.h></code>
<code><float.h></code>	<code><setjmp.h></code>	<code><stdio.h></code>	<code><wctype.h></code>



Standard library – Overview

- `<stdio.h>` – Input and output (including formatted)
- `<stdlib.h>` – Math function, dynamic memory allocation, conversion of strings to number.
 - Sorting – `qsort()`
 - Searching – `bsearch()`
 - Random numbers – `rand()`
- `<limits.h>` – Ranges of numeric types
- `<math.h>` – Math functions
- `<errno.h>` – Definition of the error values
- `<assert.h>` – Handling runtime errors

- `<ctype.h>` – character classification, e.g., see [lec06/demo-getchar.c](#)
- `<string.h>` – Strings and memory transfers, i.e., `memcpy()`
- `<locale.h>` – Internationalization
- `<time.h>` – Date and time



Standard Library (POSIX)


Relation to the operating system (OS)

POSIX – Portable Operating System Interface

- `<stdlib.h>` – Function calls and OS resources
- `<signal.h>` – Asynchronous events
- `<unistd.h>` – Processes , read/write files, ...
- `<pthread.h>` – Threads (POSIX Threads)
- `<threads.h>` – Standard thread library in C11



Advanced Programming in the UNIX Environment, 3rd edition,
W. Richard Stevens, Stephen A. Rago Addison-Wesley, 2013,
ISBN 978-0-321-63773-4



Mathematical Functions

- `<math.h>` – basic function for computing with “real” numbers

- Root and power of floating point number `x`

```
double sqrt(double x); float sqrtf(float x);
```

- `double pow(double x, double y);` – power

- `double atan2(double y, double x);` – $\arctan y/x$ with quadrant determination

- Symbolic constants – `M_PI`, `M_PI_2`, `M_PI_4`, etc.

- `#define M_PI 3.14159265358979323846`

- `#define M_PI_2 1.57079632679489661923`

- `#define M_PI_4 0.78539816339744830962`

- `isfinite()`, `isnan()`, `isless()`, ... – comparision of “real” numbers

- `round()`, `ceil()`, `floor()` – rounding and assignment to integer

- `<complex.h>` – function for complex numbers

ISO C99

- `<fenv.h>` – function for control rounding and representation according to IEEE 754.

man math



Variable Arguments <stdarg.h>

- It allows writing a function with a variable number of arguments

Similarly as in the functions printf() and scanf()

- The header file <stdarg.h> defines

- Type `va_list` and macros
 - `void va_start(va_list ap, parmN);` – initiate `va_list`
 - `type va_arg(va_list ap, type);` – fetch next variable
 - `void va_end(va_list ap);` – cleanup before function return
 - `void va_copy(va_list dest, va_list src);`

`va_copy()` has been introduced in C99

- We have to pass the number of arguments to the functions with variable number of arguments



Example – Variable Arguments <stdarg.h>

```
1 #include <stdio.h>
2 #include <stdarg.h>
3
4 int even_numbers(int n, ...);
5 int main(void)
6 {
7     printf("Number of even numbers: %i\n", even_numbers(2, 1, 2));
8     printf("Number of even numbers: %i\n", even_numbers(4, 1, 3, 4, 5));
9     printf("Number of even numbers: %i\n", even_numbers(3, 2, 4, 6));
10    return 0;
11 }
12
13 int even_numbers(int n, ...)
14 {
15     int c = 0;
16     va_list ap;
17     va_start(ap, n);
18     for (int i = 0; i < n; ++i) {
19         int v = va_arg(ap, int);
20         (v % 2 == 0) ? c += 1 : 0;
21     }
22     va_end(ap);
23     return c;
24 }
```

lec06/demo-va_args.c



Outline

Standard library – Selected Functions

Error Handling



Error handling

- Basic error codes are defined in `<errno.h>`
- These codes are used in standard library as indicators that are set in the global variable `errno` in a case of an error during the function call, e.g.,
 - If file open `fopen()` fails, it returns `NULL`, which does not provide the cause of the failure
- The cause of failure can be stored in the `errno` variable
- Text description of the numeric error codes are defined in `<string.h>`
 - String can be obtain by the function

```
char* strerror(int errnum);
```



Example – errno

■ File open

```
1 #include <stdio.h>
2 #include <errno.h>
3 #include <string.h>
4
5 int main(int argc, char *argv[]) {
6     FILE *f = fopen("soubor.txt", "r");
7     if (f == NULL) {
8         int r = errno;
9         printf("Open file failed errno value %d\n", errno);
10        printf("String error '%s'\n", strerror(r));
11    }
12    return 0;
13 }
```

lec06/errno.c

■ Program output if the file does not exist

Open file failed errno value 2
String error 'No such file or directory'

■ Program output for an attempt to open a file without having sufficient access rights

Open file failed errno value 13
String error 'Permission denied'



Testing macro assert()

- We can add tests for particular value of the variables, for debugging
- Such test can be made by the macro `assert(expr)` from `<assert.h>`
- If `expr` is not logical 1 (`true`) the program is terminated and the particular line and the name of the source file is printed
- Macro includes particular code to the program
 - It provides a relatively straightforward way to evaluate and indicate possible errors, e.g., due to a wrong function argument.*
- We can disable the macro by definition of the macro `NDEBUG`
- Example

`man assert`

```
#include <stdio.h>
#include <assert.h>

int main(int argc, char *argv[])
{
    assert(argc > 1);
    printf("program argc: %d\n", argc);
    return 0;
}
```

`lec06/assert.c`



Example of assert() Usage

- Compile the program the `assert()` macro and executing the program with/without program argument

```
clang assert.c -o assert
./assert
Assertion failed: (argc > 1), function main, file assert.c, line 5.
zsh: abort      ./assert

./assert 2
start argc: 2
```

- Compile the program without the macro and executing it with/without program argument

```
clang -DNDEBUG assert.c -o assert
./assert
program start argc: 1
./assert 2
program start argc: 2
```

lec06/assert.c



Long Jumps

- The `goto` statement can be used only within a function
- `<setjmp.h>` defines function `setjmp()` and `longjmp()` for jumps across functions
- `setjmp()` stores the actual state of the registers and if the function return non-zero value, the function `longjmp()` has been called
- During `longjmp()` call, the values of the registers are restored and the program continues the execution from the location of the `setjmp()` call

We can use `setjmp()` and `longjmp()` to implement handling exceptional states similarly as try-catch

```
1 #include <setjmp.h>
2 jmp_buf jb;
3 int compute(int x, int y);
4 void error_handler(void);
5 if (setjmp(jb) == 0) {
6     r = compute(x, y);
7     return 0;
8 } else {
9     error_handler();
10    return -1;
11 }
```

```
12 int compute(int x, int y) {
13     if (y == 0) {
14         longjmp(jb, 1);
15     } else {
16         x = (x + y * 2);
17         return (x / y);
18     }
19 }
20 void error_handler(void) {
21     printf("Error\n");
22 }
```



Communication with the Environment – <stdlib.h>

- The header file <stdlib.h> defines standard program return values EXIT_FAILURE and EXIT_SUCCESS

- A value of the environment variable get be retrieved by the getenv()

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int main(void)
5 {
6     printf("USER: %s\n", getenv("USER"));
7     printf("HOME: %s\n", getenv("HOME"));
8     return EXIT_SUCCESS;
9 }
```

lec06/demo-getenv.c

- `void exit(int status);` – the program is terminated as it will be by calling `return(status)` in the `main()` function.
- We can register a function that will be called at the program exit by the `int atexit(void (*func)(void));`
- The program can be aborted by calling `void abort(void)`, in this case, registered functions by the `atexit()` are not called



Example – atexit(), abort(), and exit()

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4
5 void cleanup(void);
6 void last_word(void);
7
8 int main(void)
9 {
10    atexit(cleanup); // register function
11    atexit(last_word); // register function
12    const char *howToExit = getenv("HOW_TO_EXIT");
13    if (howToExit && strcmp(howToExit, "EXIT") == 0) {
14        printf("Force exit\n");
15        exit(EXIT_FAILURE);
16    } else if (howToExit && strcmp(howToExit, "ABORT") ==
17                0) {
18        printf("Force abort\n");
19        abort();
20    }
21    printf("Normal exit\n");
22    return EXIT_SUCCESS;
23}
24 void cleanup(void)
25{
26    printf("Perform cleanup at the program exit!\n");
27}
28 void last_word(void)
29{
30    printf("Bye, bye!\n");
31}

```

■ Example of usage

```
clang demo-atexit.c -o atexit
```

```
% ./atexit; echo $?
```

Normal exit

Bye, bye!

Perform cleanup at the program exit!

0

```
% HOW_TO_EXIT=EXIT ./atexit; echo $?
```

Force exit

Bye, bye!

Perform cleanup at the program exit!

1

```
% HOW_TO_EXIT=ABORT ./atexit; echo $?
```

Force abort

zsh: abort HOW_TO_EXIT=ABORT ./atexit

134

lec06/demo-atexit.c



Summary of the Lecture



Topics Discussed

- I/O operations
 - File operations
 - Character oriented input/output
 - Text files
 - Block oriented input/output
 - Non-blocking input/output
 - Terminal input/output
- Selected functions of standard library
 - Overview of functions in standard C and POSIX libraries
 - Variable number of arguments
 - Error handling
- Next: Parallel programming



Topics Discussed

- I/O operations
 - File operations
 - Character oriented input/output
 - Text files
 - Block oriented input/output
 - Non-blocking input/output
 - Terminal input/output
- Selected functions of standard library
 - Overview of functions in standard C and POSIX libraries
 - Variable number of arguments
 - Error handling
- Next: Parallel programming

