

b3M33MKR: Introduction to Robots

Karel Košnar

2018






- Kobuky base
 - Control
 - Odometry
 - Bumper
 - <u>...</u>
- NUC PC
 - SSH
 - Wifi
 - ROS
- RGBD Sensor
 - Intel RealSense
 - Orbex Astra





System overview





Robot Operating System (ROS)

- Middleware that integrates, sensors, robots and logic into modular system.
- In barebones it provides communication layer between processing units.
- Suports multiple language and multiple machines.
- The main building blocks are Nodes, Topics and Services.

- Node building block of robotic system (camera driver, robot controller, image filter ...)
- Topic named stream of data with same type (rgb camera image, odometry, robot commands ...)
- Service named function, with specific request and response (reset odometry, open gripper, compute ik ...)





- Network in the KN:E130 essid: e210bot, key: j6UsAC8a
- Using ssh: ssh ros@turtle01 pass: rOsrOs
- Using ssh with ip address: ssh ros@192.168.210.21 pass: r0sr0s
- Start robot driver: turtle_start



Resources

Turtlebot

- https://gitlab.fel.cvut.cz/wagnelib/turtlebot
- http://www.turtlebot.com/turtlebot2/
- http://wiki.ros.org/Robots/TurtleBot
- http://wiki.ros.org/kobuki
- ROS
 - http://www.ros.org
 - http://wiki.ros.org
 - https://answers.ros.org