

2. tutorial in Prolog

November 21, 2021

Task 1: Load the database of the British royal family from the last tutorial into Prolog. If you've lost it, it is provided at the end of this document.

Task 2: Compare 4 implementations of `ancestor(Anc, Desc)`, which should connect parents with children, grandparents with grandchildren, grand-grandchildren with grand-grand-children, etc.

```
ancestor1(A,D) :- parent(A,D).
ancestor1(A,D) :- parent(A,B), ancestor1(B,D).

ancestor2(A,D) :- parent(A,D).
ancestor2(A,D) :- ancestor2(B,D), parent(A,B).

ancestor3(A,D) :- parent(A,B), ancestor3(B,D).
ancestor3(A,D) :- parent(A,D).

ancestor4(A,D) :- ancestor4(B,D), parent(A,B).
ancestor4(A,D) :- parent(A,D).
```

First without your computer, guess which implementation matches the behavior below. Please, verify your answers on a computer *after* you made your guess.

- a. Implementation works exactly as expected.
- b. Ends up in an infinite loop immediately.
- c. Works as expected, but finds grand-parents and grand-children before parents and children.
- d. Works as expected, but after the last response, Prolog ends up in an infinite loop.

Check your knowledge:

- What causes the infinite looping in the “bad” implementations?
- Would it help if *left-to-right* rule was changed to *right-to-left* rule?
- Or if the *top-to-bottom* rule was *bottom-to-top* rule?

Task 2: Match terms in various forms with their usual meaning.

<i>Syntactic sugar</i>	<i>Usual meaning</i>	<i>Hacker's syntax</i>
[]	list with 1 item	'.'(X,Y)
[X,Y]	empty list	'.'(harry, [])
[harry]	list with 2 items	[]
[X Y]	list with at least 1 item	'.'(X, '.'(Y, []))

Lesson learned: A list in Prolog is similar to structures in functional languages. If `L` is a list, then `[H|L]` is also a list, bigger by 1 element, where `H` is the element prepended to the beginning. You can add and/or remove elements from the beginning using the same syntax. `LL=[H|L]` both “adds” or “removes” the first element depending on whether `LL` or `L` are instantiated.

Task 3: Define basic predicates which work with lists:

- `list_of_size_one(X)` succeeds iff `X` has size exactly 1.
- `any_list(X)` succeeds iff `X` is any list. Hence `any_list(harry)` must fail, but `any_list([harry])` succeeds.
- `my_member(X, List)` succeeds iff `X` is inside the `List`. `my_member(b, [a,b,c])` must succeed and `my_member(d, [a,b,c])` must fail. If you did your implementation correctly, `my_member(X, [a,b,c])` should give you all 3 correct answers: `X=a`; `X=b`; `X=c`.

Task 4: Extend the (correct) implementation of `ancestor` so that in the 3rd argument, you get a list of people that are “between” the `Ancestor` and `Descendant`.

```
?- ancestor(diana, william, X).
X = [].

?- ancestor(elizabeth, william, X).
X = [charles].
```

See the beauty of Prolog! Ask for all grand grandparents:

```
?- ancestor(GrandGrandParent, Person, [GrandParent, Parent]).
```

Task 6: Define the `my_append(A, B, AB)` predicate. It appends list `B` to the end of list `A` and gives the result in the third argument `AB`.

```
?- my_append([a,b,c], [d,e], L).
L = [a,b,c,d,e].
```


If you did your job correctly, `my_append(L1, L2, [a, b, c])` rewards you with a surprising answer!

Lost? See the hacker's syntax of lists `[a,b,c]` and `[d,e]`:

`'.'(a, '.'(b, '.'(c, [])))` and `'.'(d, '.'(e, []))`

Look carefully. Now, the secret to `append` is:

If you remove `[]` in the *first* list and put the second list *instead*, you are done!



The `append` should recurse on the first argument, strip one item after another until it reaches an empty list. Then it does the replacement.

Still lost? What is the result of appending anything to an empty list? Start from `append([], X, ?)`...

Task 7: The main procedure behind Prolog is called *unification*. You've used it every time Prolog replaced a variable by a value (try `?- X=a`), but it's much more powerful. For example `[X,Y] = [a,b]` will "extract" values from inside the list.

The somewhat informal definition of unification is:

Two terms unify if they can be made equal only by substituting variables.

For each of these terms, put a tick \checkmark if they will unify or leave \square if they don't. If they unify, write down the substitution.

`plus(X,Y) = plus(Z,4)`

`'.'(first, '.'(second, [])) = '.'(A, '.'(B, []))`

`'.'(first, '.'(second, [])) = '.'(A,B)`

`'.'(first, []) = '.'(A, '.'(B, []))`

`'.'(X, '.'(Y, [])) = '.'(Y, '.'(element, []))`

`X = f(X)`

`unify_with_occurs_check(X,f(X))`

Task 8: Define `my_reverse(List, Reversed)` that reverses elements in a list

<pre>?- my_reverse([1,2,3,4,5], L). L = [5,4,3,2,1].</pre>
--

Don't know how to start? Use `append(List, [X], ListX)` to add an element at the end of a list.

Task 9 (optional): Use an accumulator to reduce the runtime of `my_reverse` from $\mathcal{O}(n^2)$ to $\mathcal{O}(n)$.

Task 10 (optional): Define the `descendant` and carefully observe the difference from `ancestor2` and `ancestor3` predicates in task 2.

Task 11 (optional): Extend the `my_member` predicate into the `select` predicate, which gives the “rest” of the list:

```
?- my_select(Elem, [a,b,c], Rest).  
Elem = a,  
Rest = [b, c] ;  
Elem = b,  
Rest = [a, c] ;  
Elem = c,  
Rest = [a, b] ;  
false.
```

Task 12 (optional): Rewrite the ancestor predicate so that the `Ancestor` and `Descendant` are included in the list:

```
?- ancestor(X,Y,Z).  
X = charles,  
Y = harry,  
Z = [charles, harry] ;  
X = charles,  
Y = william,  
Z = [charles, william] ;  
...
```

Task 13 (optional): Flatten a nested list.

```
?- my_flatten([[a,b], [], [c, [d,e], [f]]], X).  
X = [a, b, c, d, e, f] ; ...
```

It's enough to return additional (incorrect) answers. We'll learn how to remove them next week.

```
female(camilla).
female(diana).
female(elizabeth).
female(louise).
female(sophie).

male(charles).
male(edward).
male(george).
male(harry).
male(james).
male(philip).
male(william).

parent(charles,harry).
parent(charles,william).
parent(diana,harry).
parent(diana,william).
parent(edward,james).
parent(edward,louise).
parent(elizabeth,charles).
parent(elizabeth,edward).
parent(george,elizabeth).
parent(philip,charles).
parent(philip,edward).
parent(sophie,james).
parent(sophie,louise).

wife(camilla,charles).
wife(diana,charles).
wife(elizabeth,philip).
wife(sophie,edward).
```