

Lecture 8: Static Graphical User Interface

B0B17MTB, BE0B17MTB – MATLAB

Miloslav Čapek, Viktor Adler, Vít Losenický, *et al.*


Department of Electromagnetic Field
Czech Technical University in Prague
Czech Republic
matlab@fel.cvut.cz

November 14, 2022
Winter semester 2022/23




Outline

1. Static GUI
2. Exercises






Structure of GUI I.





Structure of GUI II.


- Object Hierarchy (simplified):





Structure of GUI III.

- Basic UI components:





Screen Properties – groot

- ▶ Corresponds to computer screen in Matlab.
- ▶ All other graphical objects are children (descendants) of Root object.
- ▶ In workspace is handle object of class `matlab.ui.Root`.
- ▶ Usually used to find out number of screens and its resolution.

```
hG = groot();  
nScreens = size(hG.MonitorPositions, 1);  
mainScreenRes = hG.ScreenSize(3:4);
```

```
>> groot  
  
ans =  
  
Show all properties  
    CallbackObject: [0x0 GraphicsPlaceholder]  
    Children: [0x0 GraphicsPlaceholder]  
    CurrentFigure: [0x0 GraphicsPlaceholder]  
    FixedWidthFontName: 'Courier New'  
    HandleVisibility: 'on'  
    MonitorPositions: [2x4 double]  
        Parent: [0x0 GraphicsPlaceholder]  
        PointerLocation: [311 870]  
        ScreenDepth: 32  
    ScreenPixelsPerInch: 96  
        ScreenSize: [1 1 1920 1200]  
    ShowHiddenHandles: off  
        Tag: ''  
        Type: 'root'  
        Units: 'pixels'  
    UserData: []
```




Graphical Window – uifigure

- ▶ Function `uifigure` creates standalone graphical window.

```
hFig = uifigure()
```

- ▶ All figures are descendants of the object `groot`.
- ▶ All secondary graphic objects are descendants of the object `figure` and are drawn in the figure.
- ▶ Object `uifigure` has many properties.
 - ▶ See `get(uifigure)`.
 - ▶ `hFig = uifigure()`.
- ▶ Figure can be closed using:
 - ▶ `hFig.delete()`, `delete(hFig)`,
 - ▶ or close `all force` (for debugging purposes!).





Position of Components


- MATLAB combines size of UI components and its position in one vector (property Position):

```
uifigure('Position', [left, bottom, width, height]);
```

- Position is absolute in pixels relative to the parent container by default.
 - Property Units of UI components set to 'pixels'.
 - uifigure, uitab and uipanel supports also 'normalized', 'centimeters', 'inches', 'characters', ...
- Creation of the figure in the center of the screen and a panel in the center of figure:

```
figSize = [400, 200];
panelSize = [300 150];
screenSize = get(groot, 'ScreenSize');
hFig = uifigure('Position', ...
    [(screenSize(3:4) - figSize)/2, figSize], ...
    'Name', 'My Application');
hPanel = uipanel(hFig, 'Position', ...
    [(figSize - panelSize)/2, panelSize], ...
    'Title', 'Panel');


hFig = uifigure('Units', 'normalized', ...
    'Position', [0.4 0.4 0.2 0.2]);
```





GUI Window Creation

- ▶ In a new script that we will be extending throughout today's lecture create a figure window that opens in the center of the screen having width of 350 pixels and height of 400 pixels.
 - ▶ Make sure the figure's Name is "Mouse Utility".
 - ▶ Change window's Color (up to you).






Container Components – uipanel

- ▶ Create panel as a parent to other objects.
- ▶ Objects inside are positioned related to the panel.
- ▶ Many features available (see >> doc `uipanel`)
- ▶ Generally, string class can be used to define properties of UI components.


```
hFig = uifigure("Name", "Figure With Panels");
hPanel1 = uipanel(hFig, "Title", "Main Panel", ...
    "FontSize", 12, "BackgroundColor", "white", ...
    "Position", [20, 20, 520, 380]);
hPanel2 = uipanel(hPanel1, "Title", "Subpanel", ...
    "TitlePosition", "centertop", ...
    "Scrollable", true, "BorderType", "none", ...
    "Position", [50 50 420 280]);
hPanel3 = uipanel(hPanel2, ...
    "Title", "Too Large Panel", ...
    "ForegroundColor", "white", ...
    "BackgroundColor", 0.4*ones(1, 3), ...
    "Position", [100 20 220 400]);
```





Panel Creation

- ▶ Into previously created figure create two panels with Position and Title:
 - ▶ [10, 330, 330, 60] px, 'Measure!',
 - ▶ [10, 70, 330, 250] px, 'Results'.
- ▶ Set proper Backgroundcolor, FontWeight, ... (up to you).






Container Components – uitab

- ▶ Creates a tab that will be parent for other objects (same as with panel).
- ▶ uitab object has to be children of uitabgroup object.
 - ▶ Manage the tab switching, title positioning, ...

```
hFig = uifigure('Name', 'Figure With Tabs');
hTabGroup = uitabgroup(hFig, ...
    'Position', [20, 20, 520, 380], ...
    'TabLocation', 'left');
hTab1 = uitab(hTabGroup, 'Title', 'Tab 1');
hTab2 = uitab(hTabGroup, 'Title', 'Tab 2', ...
    'BackgroundColor', 'k', ...
    'ForegroundColor', 'w');
hTab3 = uitab(hTabGroup, 'Title', 'Tab 3', ...
    'Scrollable', true);
hPanel = uipanel(hTab3, ...
    'Title', 'Too Large Panel', ...
    'Position', [20, 150, 600, 200]);
hTabGroup.SelectedTab = hTab3;
```






Container Components – uigridlayout

- ▶ Grid layout manage position UI components along the rows and columns of an invisible grid that spans the entire figure or a container within the figure.
- ▶ Gradually added components are placed in column-wise order (as with subplot).
- ▶ It is always possible to edit Layout property of children component to place it to arbitrary cell.

```
hFig = uifigure('Name', 'Figure With Grig Layout');
hGrid = uigridlayout(hFig, ...
    'ColumnWidth', {200, 'lx'}, ...
    'RowHeight', {'lx', '2x'});
hPanel1 = uipanel(hGrid, 'Title', 'Panel 1');
hPanel2 = uipanel(hGrid, 'Title', 'Panel 2');

hTabGrop = uitabgroup(hGrid);
hTabGrop.Layout.Column = 2;
hTabGrop.Layout.Row = 2;
uitab(hTabGrop, 'Title', 'Tab 1');
uitab(hTabGrop, 'Title', 'Tab 2');

hPanel3 = uipanel(hGrid, 'Title', 'Panel 3');
hPanel3.Layout.Row = 2;
hPanel3.Layout.Column = 1;
```






Container Components – uibuttongroup

- ▶ Create button group to manage radio buttons and toggle buttons.
 - ▶ It is not possible to mix these objects in one button group.
- ▶ The children of a button group object can be beside that any UI component.

```
hFig = uifigure('Name', 'Figure With Button Group', ...
    'Position', [200 200 250 170]);
hGroup = uibuttongroup(hFig, 'Position', [10, 10, 230, 150], ...
    'Title', 'Toggle Button Group');
hButt1 = uitogglebutton(hGroup, 'Text', 'Option 1', ...
    'Position', [10 90 100 30]);
hButt2 = uitogglebutton(hGroup, 'Text', 'Option 2', ...
    'Position', [10 50 100 30]);
hButt3 = uitogglebutton(hGroup, 'Text', 'Option 3', ...
    'Position', [10 10 100 30]);
hPanel = uipanel(hGroup, 'Title', 'Panel', ...
    'Position', [120, 10, 100, 110]);
```




```
%% Selection via button group
hGroup.SelectedObject = hButt2;
% or use button Value property
hButt2.Value = true;
% get values
values = [hGroup.Buttons.Value]
```



Figure Menu – uimenu

- ▶ Create figure menu items with arbitrary hierarchy.
- ▶ Mnemonic keyboard shortcut ($\text{Alt} + \text{mnemonic}$) by using the ampersand (&) character in the text for the label.
 - ▶ To use mnemonics, you must specify a mnemonic for all menus and menu items.
- ▶ Accelerator define a keyboard shortcut for selecting a menu item ($\text{Ctrl} + \text{acc.}$).

```
hFig = uifigure('Name', 'Figure with Menu', ...
    'Position', [200, 200, 350, 110]);
hMenuFile = uimenu(hFig, 'Text', '&File');
hMenuOpen = uimenu(hMenuFile, 'Text', '&Open', ...
    'Accelerator', 'O');
hMenuSave = uimenu(hMenuFile, 'Text', '&Save ...');
hMenuSaveAll = uimenu(hMenuSave, 'Text', 'Save &All', ...
    'Accelerator', 'S');
hMenuSaveAs = uimenu(hMenuSave, 'Text', 'Sav&e As...');
hMenuClose = uimenu(hMenuFile, 'Text', '&Close', ...
    'Accelerator', 'C', 'Separator', true);
hMenuHelp = uimenu(hFig, 'Text', '&Help');
hMenuShowHelp = uimenu(hMenuHelp, 'Text', 'Show &Help');
hMenuWhisper = uimenu(hMenuHelp, 'Text', 'Whis&per', ...
    'Checked', true);
```






Context Menu – uicontextmenu

- ▶ Context menu is invoked by right-click on an assigned UI object.
- ▶ To assign the context menu to the UI object set its `ContextMenu` property.
- ▶ Individual items in context menu are `uimenu` objects.
- ▶ Accelerator shortcuts works even when the context menu is not shown.

```
hFig = uifigure('Name', 'Figure with Context Menu', ...
    'Position', [200, 200, 350, 130]);
hContMenu = uicontextmenu(hFig);
hMenuOpen = uimenu(hContMenu, 'Text', 'Open', ...
    'Accelerator', 'O');
hMenuSave = uimenu(hContMenu, 'Text', 'Save ...');
hMenuSaveAll = uimenu(hMenuSave, 'Text', 'Save All', ...
    'Accelerator', 'S');
hMenuSaveAs = uimenu(hMenuSave, 'Text', 'Save As...');
hMenuClose = uimenu(hContMenu, 'Text', 'Close', ...
    'Accelerator', 'C', 'Separator', true);
%% Assign menu to proper object
hFig.ContextMenu = hContMenu;
%% Open menu programmatically
% at specified position of low left corner
open(hContMenu, 10, 10);
```






Graph Area – uiaxes

- ▶ Defines area where descendants of object uiaxes are placed.
- ▶ Axes is created using uiaxes command even without actual existence of parental uifigure object.
- ▶ uiaxes object has many properties, try get(uiaxes), or properties(uiaxes).

```
hFig = uifigure('Name', 'Figure with Axes');
hAx = uiaxes(hFig, ...
    'Position', [20, 20, 520, 380]);
hAx.Toolbar.Visible = false;
surf(hAx, peaks);
```

- ▶ Usual plotting functions as plot, surf, pcolor, stem, ... support uiaxes objects.
- ▶ It is always necessary to provide uiaxes reference, e.g.:

```
plot(hAx, rand(10, 5));
```






Fast Graphics Update

- ▶ Graphics made from user interface (UI) components is significantly slower than graphics made within "old" figure.
- ▶ drawnow and pause works in the same way as with figure.

```
f0 = 1e9;
x = linspace(0, 1, 201);
y = x.';
c0 = 3e8;
lambda = c0/f0;
t = linspace(0, 1/f0);
k = 2*pi/lambda;
R = sqrt(x.^2 + y.^2);
```

```
hFig = uifigure;
hAx = uiaxes('Parent', hFig, 'Position', [10 10 540 400]);
hSurf = surf(hAx, 'Parent', hAx, 'LineStyle', 'none', ...
    'XData', x, 'YData', y, 'ZData', nan(size(R)));
drawnow();
tic;
for thisTime = t
    E = exp(1j*(-k*R + 2*pi*f0*thisTime));
    hSurf.ZData = real(E);
    drawnow();
end
tEnd = toc;
fprintf('Reached FPS: %.2f Hz.\n', length(t)/tEnd);
```





UI Components – uilabel

- ▶ Labels contain static text for labelling parts of an application.
- ▶ Property Interpreter can be '`tex`', '`latex`' and '`html`' for additional formatting.
- ▶ Labels can be children of all UI containers.
- ▶ All UI component labels and titles can contain unicode characters (`char(uniNumber)`).
 - ▶ Can be found, e.g., here: <http://unicode-table.com/>.


```
hFig = uifigure('Name', 'Figure with Label', ...
    'Position', [200, 200, 400, 100]);
hLabel = uilabel(hFig, 'Text', ...
    ['Fancy Label with ', char(960)], ...
    'HorizontalAlignment', 'Center', ...
    'Position', [10, 10, 380, 80], ...
    'FontName', 'Times New Roman', ...
    'FontSize', 40, ...
    'FontWeight', 'bold', ...
    'FontAngle', 'italic', ...
    'FontColor', 'm', ...
    'BackGroundColor', 0.3*ones(1, 3));
```





Label Creation

- ▶ Create two labels into panel called '**Results**' with Position and Text properties as:
 - ▶ [10, 200, 90, 20], 'Wheel Count:',
 - ▶ [10, 180, 120, 20], 'Cursor Speed (px/s):'.
- ▶ Set proper Backgroundcolor, FontWeight, ... (up to you).






UI Components – uieditfield

- ▶ Create text or numeric edit field component.
- ▶ Function `uieditfield` or `uieditfield('text')` creates edit field handling strings.
 - ▶ See >> doc `EditField` for formatting possibilities.
- ▶ Function `uieditfield('numeric')` creates edit field handling numerical values.
 - ▶ Moreover offers rounding, limits and format (see >> doc `NumericEditField`).

```

hFig = uifigure('Name', 'Figure with Edit Fields', ...
    'Position', [200, 200, 400, 130]);
hEdit1 = uieditfield(hFig, 'numeric', 'Value', pi, ...
    'Position', [10, 70, 280, 50], ...
    'Limits', [-10, 10], ...
    'ValueDisplayFormat', '%.2e V/m', ...
    'FontSize', 30);
hEdit2 = uieditfield(hFig, 'text', ...
    'Value', 'log10(abs(X))', ...
    'HorizontalAlignment', 'center', ...
    'FontSize', 30, 'Position', [10, 10, 280, 50], ...
    'FontColor', 'r', 'BackgroundColor', 'k');
% value regardless of display format:
setValue = hEdit1.Value


```





Edit Field Creation

- ▶ In panel titled '**Results**' create numeric edit box with Position property as [120, 200, 90, 22] px.
- ▶ Set proper Backgroundcolor, FontWeight, ... (up to you).





UI Components – uibutton

- ▶ Create push button or state button component.
- ▶ The state button can be done by `style` argument as `uibutton('state')`.
 - ▶ It is not the same as `uitogglebutton`, can't be managed by `uibuttongroup`!
- ▶ Icon can be defined also as m-by-n-by-3 truecolor image array.
- ▶ Properties can be aggregated into a cell array and used as comma-separated list by `{ : }` as function inputs (holds generally).


```

buttProperties = {'Text', 'OK', ...
    'Position', [70, 10, 90, 65], ...
    'Icon', 'ngc6543a.jpg', ...
    'IconAlignment', 'top', ...
    'FontWeight', 'bold', ...
    'ToolTip', 'Click me!'};
```

`hFig = uifigure('Position', [200, 200, 230, 85]);`

`hButt = uibutton(hFig, buttProperties{:});`



```
% Icon as a random color image
hButt.Icon = uint8(rand(20, 20, 3)*255);
```





Push Button Creation

- ▶ Create push button labelled '**Close**' positioned in figure with Position property [130, 20, 90, 30] px.
- ▶ Set proper Backgroundcolor, FontWeight, ... (up to you).






UI Components – uiswitch

- ▶ Create slider switch, rocker switch, or toggle switch component.
- ▶ All switches can be oriented vertically or horizontally (Orientation property).
- ▶ Labels can be modified (Items property).

```
hFig = uifigure('Name', 'Switches', ...
    'Position', [200, 200, 225, 300]);
hGrid = uigridlayout(hFig, ...
    'ColumnWidth', {'1x', '1x'}, ...
    'RowHeight', {'1x', '1x', '1x'});
hSwitch1 = uiswitch(hGrid, 'slider', ...
    'Orientation', 'horizontal', ...
    'Items', {'0', '1'}, 'ItemsData', {false, true});
uiswitch(hGrid, 'slider', 'Orientation', 'vertical');

uiswitch(hGrid, 'rocker', 'Orientation', 'horizontal');
uiswitch(hGrid, 'rocker', 'Orientation', 'vertical');


uiswitch(hGrid, 'toggle', 'Orientation', 'horizontal');
uiswitch(hGrid, 'toggle', 'Orientation', 'vertical');
% Value as corresponding 'ItemsData' element
logValue = hSwitch1.Value
```





Switch Creation

- ▶ Create switch positioned in panel titled '**Measure!**' with Position property [140, 10, 100, 25] px, Items as {'Off', 'On'} and ItemsData as [false, true].
- ▶ Set proper Style, Items, FontWeight, ... (up to you).






UI Components – uigauge

- ▶ Create gauge component for indicating numerical value.
- ▶ Several *style* options `uigauge (style)`:
 - ▶ `'circular'`, `'linear'`, `'ninetydegree'`, `'semicircular'`.
 - ▶ Different orientation possibilities (`'counterclockwise'`, `'north'`, `'vertical'`, ...).

```

hFig = uifigure('Name', 'Gauges', ...
    'Position', [200, 200, 220, 450]);
hGrid = uigridlayout(hFig, ...
    'ColumnWidth', {'1x'}, ...
    'RowHeight', {'1x', '1x', '0.5x', '1.2x'});
uigauge(hGrid, 'circular', ...
    'Limits', [-pi, pi], ...
    'ScaleDirection', 'counterclockwise', ...
    'MajorTicks', -pi:pi:pi, ...
    'MajorTickLabels', ...
    {char(960), '0', ['-'], char(960)}, ...
    'FontSize', 20);
uigauge(hGrid, 'ninetydegree', ...
    'ScaleColors', {'b', 'g', 'r'});
uigauge(hGrid, 'linear', 'Value', 60);
uigauge(hGrid, 'semicircular', ...
    'BackgroundColor', 0.8*ones(1, 3));


```





Gauge Creation


- ▶ Create gauge with proper style, Limits [0 2e3] and Position [10, 10, 310, 170] px in panel titled '**Results**'.
- ▶ You can freely change display settings.





Save Static GUI

- ▶ Save creation of static GUI as a script or as a function for later use (the next lecture).






UI Components – uicheckbox

- ▶ UI component for indicating the state of a preference or option.
- ▶ Can be children of any container component.
- ▶ Always has the same background color as BackgroundColor property of parent container.

```
hFig = uifigure('Position', ...
[200, 200, 200, 70]);
hCheck1 = uicheckbox(hFig, ...
'Text', 'Right Choice', ...
'Position', [10, 40, 100, 20], ...
'Tooltip', 'Select me!');
hCheck2 = uicheckbox(hFig, ...
'Value', true, ...
'Text', 'Select Option', ...
'FontName', 'Courier New', ...
'FontSize', 20, ...
'FontWeight', 'bold', ...
'FontAngle', 'italic', ...
'FontColor', 'r', ...
'Position', [10, 10, 180, 30]);
```






UI Components – uiradiobutton

- ▶ Create radio button within a button group (`uibuttongroup`).
- ▶ Only one radio button can be selected.
- ▶ Always has the same background color as `BackgroundColor` property of parent container.

```
hFig = uifigure('Name', 'Figure with Button Group', ...
    'Position', [200 200 250 170]);
hGroup = uibuttongroup(hFig, 'Position', [10, 10, 230, 150], ...
    'Title', 'Radio Button Group');
hButt1 = uiradiobutton(hGroup, 'Text', 'Option 1', ...
    'Position', [10 90 100 30]);
hButt2 = uiradiobutton(hGroup, 'Text', 'Option 2', ...
    'Position', [10 50 100 30]);
hButt3 = uiradiobutton(hGroup, 'Text', 'Option 3', ...
    'Position', [10 10 100 30]);
hPanel = uipanel(hGroup, 'Title', 'Panel', ...
    'Position', [120, 10, 100, 110]);
```

```
% Button selection programmatically:
hButt2.Value = true;
% or
hGroup.SelectedObject = hButt2;
```






UI Components – uilistbox

- ▶ UI component for displaying items in a list.
- ▶ It is possible to select more options using Ctrl and Shift key.
- ▶ It is possible to get the selected items via Value property.
 - ▶ Values are elements from ItemsData vector, if defined.

```
hFig = uifigure('Name', 'Figure with List Box', ...
    'Position', [200 200 200 110]);
hList = uilistbox(hFig, 'Position', [10, 10, 70, 90], ...
    'Items', {'Item 1','Item 2','Item 3','Item 4'}, ...
    'Multiselect', true);
```

```
% get selected items from Items vector
selItems = hList.Value
% get selected items from ItemsData vector
hList.ItemsData = 1:4;
selItems = hList.Value
```







UI Components – uidropdown

- ▶ UI component that enable the user to select an option.
- ▶ Only one option can be selected.

```
hFig = uifigure('Name', 'Figure with Drop Down', ...
    'Position', [200 200 200 140]);
hList = uidropdown(hFig, 'Position', [10, 105, 70, 25], ...
    'Items', {'Item 1','Item 2','Item 3','Item 4'});
```

```
% get selected item from Items vector
selItems = hList.Value
% get selected item from ItemsData vector
hList.ItemsData = 1:4;
selItems = hList.Value
```






UI Components – uislider

- ▶ UI component that allow the user to select a value along a continuum.
- ▶ Orientation can be '`'horizontal'` or '`'vertical'`.
 - ▶ Height, or width, respectively, can't be changed and is always 3 px.
 - ▶ Position property define position of slider excluding tick marks and tick labels.
 - ▶ OuterPosition property (read-only) is position of the whole slider.

```
hFig = uifigure('Name', 'Figure with Slider', ...
    'Position', [200, 200, 200, 400], ...
    'Scrollable', true, 'AutoResizeChildren', false);
hSlider = uislider(hFig, 'Limits', [-100, 100], ...
    'Orientation', 'vertical', ...
    'Position', [20, 20, 3, 360], ...
    'FontSize', 30, ...
    'MajorTicks', -100:50:100, ...
    'Value', -30);

hSlider.OuterPosition
```






UI Components – uispanner

- ▶ UI component for selecting numeric value from a finite set.
- ▶ Offers rounding, limits, step and format (see >> doc `Spinner`).
- ▶ Value property contains setted value regardless display format.

```
hFig = uifigure('Name', 'Figure with Spinner', ...
    'Position', [200, 200, 200, 55]);
hSpinner = uispanner(hFig, 'Value', pi, ...
    'Limits', [-10, 10], ...
    'Step', 5, ...
    'ValueDisplayFormat', '%.1f px', ...
    'FontColor', 'white', ...
    'BackgroundColor', [0 0 0], ...
    'ToolTip', 'Set shift in pixels', ...
    'Position', [10, 15, 100, 25]);
value = hSpinner.Value
```






UI Components – uiknob

- ▶ UI components representing instrument control knobs that the user can adjust to control a value.
- ▶ `uiknob()` and `uiknob('continuous')` creates knob with continuous values.
- ▶ `uiknob('discrete')` creates knob with discrete values.
 - ▶ Value, Items and ItemsData properties works the same way as for, e.g., uidropdown.

```
hFig = uifigure('Name', 'Figure with Knobs', ...
    'Position', [200, 200, 200, 300]);
hKnob1 = uiknob(hFig, 'discrete', 'Items', ...
    {'Apple', 'Potatoes', 'MANA', 'Steak'}, ...
    'ItemsData', 1:4, ...
    'Value', 2, ...
    'Position', [60, 170, 80, 140]);
hKnob2 = uiknob(hFig, ...
    'Position', [50, 30, 100, 140], ...
    'Value', 20, ...
    'Limits', [-50, 50]);
```





UI Components – uitable

- ▶ Create table user interface component.
- ▶ Table offer many of formatting and interactive options (see >> doc `uitable`).

```
hFig = uifigure('Name', 'Figure with Table', ...
    'Position', [200, 200, 330, 330]);
% simple table:
hTab1 = uitable(hFig, 'Data', magic(10), ...
    'Position', [10 110 310 210]);
% advanced table:
hTab2 = uitable(hFig, 'Data', ...
    {'Smith', 38, 'Choose', true;
    'Johnson', 43, 'Choose', false;
    'Williams', 38, 'Choose', false}, ...
    'ColumnName', ...
    {'Name', 'Age', 'Personality', ...
    'Authorized'}, ...
    'ColumnFormat', ({[], [], {'Analyst', ...
    'Diplomat', 'Explorer', 'Idiot'}}, []),
    'ColumnWidth', {50, 50, 90, 70}, ...
    'Position', [10 10 310 90], ...
    'ColumnEditable', true(1, 4));
```

The screenshot shows a MATLAB figure window titled "Figure with Table". It contains two "uitable" components. The top one is a standard 10x4 matrix of integers from 1 to 99. The bottom one is a more complex table with columns for Name, Age, Personality, and Authorized status. The "Authorized" column contains checkboxes, some of which are checked (e.g., for "Smith").

	1	2	3	4
1	92	99	1	
2	98	80	7	
3	4	81	88	
4	85	87	19	
5	86	93	25	
6	17	24	76	
7	23	5	82	
8	79	6	13	
9	10	12	94	


	Name	Age	Personality	Authorized
1	Smith	38	Choose	<input checked="" type="checkbox"/>
2	Johnson	43	Choose	<input type="checkbox"/>
3	Williams	38	Choose	<input type="checkbox"/>



UI Components – uitextarea

- ▶ UI component for entering multiple lines of text.
- ▶ If the text does not fit into the width of the text area, the text is wrapped.

```
hFig = uifigure('Name', 'Figure with Text Area', ...
    'Position', [200, 200, 200, 100]);
hText = uitextarea(hFig, 'Value', ...
    ["Type Your Name"; "Technicka 2"; "Prague 6";
    "166 27"; "Czech Republic"], ...
    'FontName', 'Courier New', ...
    'FontColor', [0.1, 0.1, 1], ...
    'Position', [10, 10, 180, 80]);
% get entered address
yourAddress = hText.Value
```






UI Components – uilamp

- ▶ Lamp is UI component that indicates state using color.

```
hFig = uifigure('Name', 'Figure with Lamps', ...
    'Position', [200, 200, 200, 560], ...
    'Color', 'k');
hLamp1 = uilamp(hFig, 'Color', [1 0 0], ...
    'Position', [20, 380, 160, 160]);
hLamp2 = uilamp(hFig, 'Color', [1 0.5 0.25], ...
    'Position', [20, 200, 160, 160]);
hLamp3 = uilamp(hFig, 'Color', [0 1 0], ...
    'Position', [20, 20, 160, 160]);
% Turn the light off
hLamp1.Enable = false;
```





UI Components – uitree

- ▶ Create tree component capable of showing data hierarchy.
- ▶ Individual items in tree are objects created by uitreenode.
 - ▶ The nodes has to be children of uitree object.
 - ▶ Items can have Icon defined as path to a figure.

```


hFig = uifigure('Name', 'Figure with Tree', ...
    'Position', [200, 200, 200, 170]);
hTree = uitree(hFig, 'Position', [10 10 180 150]);

category1 = uitreenode(hTree, 'Text', 'Runners', ...
    'Icon', 'ngc6543a.jpg');
p1 = uitreenode(category1, 'Text', 'Joe');
p2 = uitreenode(category1, 'Text', 'Linda');

category2 = uitreenode(hTree, 'Text', 'Cyclists', ...
    'Icon', 'ngc6543a.jpg');
p3 = uitreenode(category2, 'Text', 'Rajeev');
p4 = uitreenode(category2, 'Text', 'Anne');

% Expand the tree
expand(hTree);

```







UI Components – uidatepicker

- ▶ Date pickers allow users to select dates from an interactive calendar.
- ▶ Accepts and returns datetime objects (see >> doc `datetime`).
- ▶ Some dates and days in week can be disabled.

```
hFig = uifigure('Name', ...
    'Figure with Date Picker', ...
    'Position', [200, 200, 280, 250]);
hDate = uidatepicker(hFig, ...
    'Value', datetime('today'), ...
    'Position', [10, 210, 150, 25], ...
    'DisabledDaysOfWeek', [6, 7]);
% get selected date
setDate = hDate.Value
```






UI Components – uiimage

- ▶ UI component that allow you to display an picture in your app.
- ▶ Can be children of any container component.

```
hFig = uifigure('Name', ...
    'Figure with Image', ...
    'Position', [200, 200, 260, 280]);
hImage = uiimage(hFig, ...
    'ImageSource', 'ngc6543a.jpg', ...
    'Position', [10, 10, 240, 260]);
```





UI Components – uitoolbar, uipushtool, uitoggletool

- ▶ A toolbar is a container for a horizontal list of buttons at the top of a figure window.
- ▶ Can contain push buttons and toggle buttons.
- ▶ Does not provide management of the toggle tools.



```

iconFolder = fullfile(matlabroot, 'toolbox', 'matlab', 'icons');
hFig = uifigure('Position', [200, 200, 180, 40]);
hTool = uitoolbar(hFig);
hPushNew = uipushtool(hTool, 'Icon', fullfile(iconFolder, 'file_new.png'), ...
    'ToolTip', 'Open File');
hPushSave = uipushtool(hTool, 'Icon', fullfile(iconFolder, 'file_save.png'), ...
    'ToolTip', 'Save File');
hPushOpen = uipushtool(hTool, 'Icon', fullfile(iconFolder, 'file_open.png'), ...
    'ToolTip', 'Open File');
hToggPlay = uitoggletool(hTool, 'Icon', fullfile(iconFolder, 'greenarrowicon.gif'), ...
    'State', true, 'Separator', true, 'Tooltip', 'Play');
hToggZoom = uitoggletool(hTool, 'Icon', fullfile(iconFolder, 'view_zoom_in.gif'), ...
    'ToolTip', 'Zoom');


% Set state of toggletool programmatically
hToggZoom.State = true;

```



Enabling UI Components

- ▶ Majority of UI components have `Enable` property which define its operational state.
- ▶ Possible values are '`on`' and '`off`', or `true` and `false`.
- ▶ When the component is disabled it doesn't response to events.
- ▶ It is also possible to let the component disappear using `Visible` property.





Preallocation of UI Components

- ▶ Function `gobjects` initialize array of graphical objects.
 - ▶ It has the same usage as function `zeros`, `ones`, ... for numeric values.


```
>> hObjs = gobjects(3, 1)

hObjs =

3x1 GraphicsPlaceholder array:
```

```
GraphicsPlaceholder
GraphicsPlaceholder
GraphicsPlaceholder
```


```
hObjs(1) = uifigure();
hObjs(2) = uiaxes(hObjs(1));
hObjs(3) = line(hObjs(2));
```





App Designer

- ▶ App Designer is a development environment that provides interactive design of application using UI components.
 - ▶ appdesigner
 - ▶ Designed application use object oriented programming (OOP).
 - ▶ It is possible to use App Designer for a semester projects.



Exercises



Exercise I.a

- ▶ Create function with two inputs and one output:

```
function logicState = createButtons(nRows, nColumns)
% function generating GUI with state buttons
```

- ▶ Function creates figure with state buttons arranged in matrix $nRows \times nColumns$.
- ▶ After clicking on state buttons and close window function returns matrix of logical values representing state of state buttons.

```
>> logicState = createButtons(3, 5)

logicState =

3x5 logical array

1 0 1 0 1
0 1 0 1 0
1 0 1 0 1
```



Exercise I.b



Questions?

B0B17MTB, BE0B17MTB – MATLAB
matlab@fel.cvut.cz

November 14, 2022
Winter semester 2022/23

This document has been created as a part of BE0B17MTB course.
Apart from educational purposes at CTU in Prague, this document may be reproduced, stored, or transmitted
only with the prior permission of the authors.
Acknowledgement: Filip Kozák, Pavel Valtr, Michal Mašek.