

AE4M33RZN, Fuzzy logic: Fuzzy description logic

Radomír Černoč

radomir.cernoch@fel.cvut.cz

11/11/2013

Faculty of Electrical Engineering, CTU in Prague

Plan of the lecture

Revision of crisp description logic

Language \mathcal{SHIF}

Concepts and interpretation

Notion of truth

Fuzzy description logic

Concepts

Notion of truth

Queries

Homework

Bibliography

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{I}
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H} = role hierarchies

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H} = role hierarchies
- \mathcal{I} = inverse properties
- \mathcal{F}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H} = role hierarchies
- \mathcal{I} = inverse properties
- \mathcal{F}
 - concept intersection
 - universal restrictions
 - limited existential quantification
 - role restriction
- \mathcal{D}

Our treatment of fuzzy description logic is based on a family of crisp description logic $\mathcal{SHIF}(\mathcal{D})$ [Baader, 2003]:

- \mathcal{AL}
 - atomic negation
 - intersection
 - universal restrictions
 - limited existential quantification
- \mathcal{C} = full concept negation
- \mathcal{S} = \mathcal{ALC} + transitive roles
- \mathcal{H} = role hierarchies
- \mathcal{I} = inverse properties
- \mathcal{F}
 - concept intersection
 - universal restrictions
 - limited existential quantification
 - role restriction
- \mathcal{D} = data types

Let A and R be the sets of *atomic concepts* and *atomic roles*.

Concept constructors

$C, D := \top \mid \perp$	top and bottom concepts	(1)
$\mid A$	atomic concept	(2)
$\mid \neg C$	concept negation	(3)
$\mid C \sqcap D$	intersection	(4)
$\mid C \sqcup D$	concept union	(5)
$\mid \forall R \cdot C$	full universal quantification	(6)
$\mid \exists R \cdot C$	full existential quantification	(7)

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$. We use the set of individuals I :

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$. We use the set of individuals I :

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \rangle$
and *role assertions* $\langle (i, j \in I) : r \in R \rangle$.

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$. We use the set of individuals I :

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \rangle$
and *role assertions* $\langle (i, j \in I) : r \in R \rangle$.

$\mathcal{T}Box$ (Terminology Box)

Contains *general concept inclusion* (GCI) axioms $\langle C \sqsubseteq D \rangle$ and role axioms (role hierarchy $\langle R_1 \sqsubseteq R_2 \rangle$, transitivity, ...).

Crisp description logic interpretation

Interpretation \mathcal{I} is a tuple $(\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$ (*interpretation domain, interpretation function*), which maps

an individual to domain object

$$i^{\mathcal{I}} \in \Delta^{\mathcal{I}}$$

an atomic concept to domain subsets

$$C^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$$

an atomic role to subset of domain tuples

$$R^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$$

Crisp description logic interpretation

The non-atomic concepts are interpreted as follows:

non-atomic concept	its interpretation
\top	$\Delta^{\mathcal{F}}$
\perp	\emptyset
$\neg C$	$\Delta^{\mathcal{F}} \setminus C^{\mathcal{F}}$
$C \sqcap D$	$C^{\mathcal{F}} \cap D^{\mathcal{F}}$
$C \sqcup D$	$C^{\mathcal{F}} \cup D^{\mathcal{F}}$
$\forall R \cdot C$	$\{x \mid \forall y \in \Delta^{\mathcal{F}}. ((x, y) \in R^{\mathcal{F}}) \Rightarrow (y \in C^{\mathcal{F}})\}$
$\exists R \cdot C$	$\{x \mid \exists y \in \Delta^{\mathcal{F}}. ((x, y) \in R^{\mathcal{F}}) \wedge (y \in C^{\mathcal{F}})\}$

Axiom satisfaction

axiom	satisfied when
$\langle i : C \rangle$	$i^{\mathcal{F}} \in C^{\mathcal{F}}$
$\langle (i, j) : R \rangle$	$(i^{\mathcal{F}}, j^{\mathcal{F}}) \in R^{\mathcal{F}}$
$\langle C \sqsubseteq D \rangle$	$C^{\mathcal{F}} \sqsubseteq D^{\mathcal{F}}$
transitive(R)	$R^{\mathcal{F}}$ is transitive
...	

- Concept C is *satisfiable*

- Concept C is *satisfiable* iff there is an interpretation \mathcal{I} s.t. $\mathcal{I} \models \langle i : C \rangle$ for some i .
- Interpretation \mathcal{I} *satisfies* a knowledgebase $\mathcal{K} = \mathcal{A}\text{Box} + \mathcal{T}\text{Box}$ (or \mathcal{I} is a *model* of \mathcal{K})

- Concept C is *satisfiable* iff there is an interpretation \mathcal{I} s.t. $\mathcal{I} \models \langle i : C \rangle$ for some i .
- Interpretation \mathcal{I} *satisfies* a knowledgebase $\mathcal{K} = \mathcal{A}\text{Box} + \mathcal{T}\text{Box}$ (or \mathcal{I} is a *model* of \mathcal{K}) iff \mathcal{I} satisfies all its axioms.
- Axiom T is a *logical consequence* of \mathcal{K}

- Concept C is *satisfiable* iff there is an interpretation \mathcal{I} s.t. $\mathcal{I} \models \langle i : C \rangle$ for some i .
- Interpretation \mathcal{I} *satisfies* a knowledgebase $\mathcal{K} = \mathcal{A}Box + \mathcal{T}Box$ (or \mathcal{I} is a *model* of \mathcal{K}) iff \mathcal{I} satisfies all its axioms.
- Axiom T is a *logical consequence* of \mathcal{K} iff every model of \mathcal{K} satisfies T . We write $\mathcal{K} \models T$.

Basic idea

Basic idea

1. Keep the the previous slides intact.

Basic idea

1. Keep the the previous slides intact.
2. Add \circ below and above every operation.

Basic idea

1. Keep the the previous slides intact.
2. Add \circ below and above every operation.
3. Watch the semantic change.

We will show the **fuzzyDL** reasoner [Bobillo and Straccia, 2008] capabilities, which extends the $\mathcal{SHIF}(\mathcal{D})$ family with fuzzy capabilities.

Concept constructors

We start with atomic concepts A . Derived concepts are on the next slide together with their interpretation. (Each concept is interpreted as a fuzzy subset of the domain.)

Fuzzy interpretation \mathcal{I} is a tuple $\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}}$ which maps

an individual to a domain object

$$i^{\mathcal{I}} \in \Delta^{\mathcal{I}}$$

an atomic concept to a domain subsets

$$C^{\mathcal{I}} \in \mathbb{F}(\Delta^{\mathcal{I}})$$

an atomic role to a relation on the domain

$$R^{\mathcal{I}} \in \mathbb{F}(\Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}})$$

$C, D :=$	interpretation of x
\perp	0
\top	1
A	$A^{\mathcal{F}}(x)$
$\neg C$	$\neg C^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
\perp	$\mathbf{0}$
\top	$\mathbf{1}$
A	$A^{\mathcal{F}}(x)$
$\neg C$	$\overline{\neg}_S C^{\mathcal{F}}(x)$
$C \square_S D$	$C^{\mathcal{F}}(x) \wedge_S D^{\mathcal{F}}(x)$
$C \square_L D$	$C^{\mathcal{F}}(x) \wedge_L D^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
\perp	$\mathbf{0}$
\top	$\mathbf{1}$
A	$A^{\mathcal{F}}(x)$
$\neg C$	$\overline{S} C^{\mathcal{F}}(x)$
$C \underset{S}{\square} D$	$C^{\mathcal{F}}(x) \underset{S}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{L}{\square} D$	$C^{\mathcal{F}}(x) \underset{L}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{S}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{S}{\vee} D^{\mathcal{F}}(x)$
$C \underset{L}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{L}{\vee} D^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
\perp	$\mathbf{0}$
\top	$\mathbf{1}$
A	$A^{\mathcal{F}}(x)$
$\neg C$	$\overline{S} C^{\mathcal{F}}(x)$
$C \underset{S}{\square} D$	$C^{\mathcal{F}}(x) \underset{S}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{L}{\square} D$	$C^{\mathcal{F}}(x) \underset{L}{\wedge} D^{\mathcal{F}}(x)$
$C \underset{S}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{S}{\vee} D^{\mathcal{F}}(x)$
$C \underset{L}{\sqcup} D$	$C^{\mathcal{F}}(x) \underset{L}{\vee} D^{\mathcal{F}}(x)$
$C \underset{S}{\overset{R}{\mapsto}} D$	$C^{\mathcal{F}}(x) \overset{R}{\underset{S}{\Rightarrow}} D^{\mathcal{F}}(x)$
$C \underset{L}{\overset{R}{\mapsto}} D$	$C^{\mathcal{F}}(x) \overset{R}{\underset{L}{\Rightarrow}} D^{\mathcal{F}}(x)$
$C \underset{S}{\overset{S}{\mapsto}} D$	$C^{\mathcal{F}}(x) \overset{S}{\underset{S}{\Rightarrow}} D^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
$\exists R \cdot C$	$\sup_y R^{\mathcal{F}}(x, y) \underset{\circ}{\wedge} C^{\mathcal{F}}(y)$
$\forall R \cdot C$	$\inf_y R^{\mathcal{F}}(x, y) \underset{\circ}{\Rightarrow} C^{\mathcal{F}}(y)$

$C, D :=$	interpretation of x
$\exists R \cdot C$	$\sup_y R^{\mathcal{F}}(x, y) \underset{\circ}{\wedge} C^{\mathcal{F}}(y)$
$\forall R \cdot C$	$\inf_y R^{\mathcal{F}}(x, y) \underset{\circ}{\Rightarrow} C^{\mathcal{F}}(y)$
$(n C)$ $\text{mod}(C)$	$n \cdot C(x)$ $\text{mod}(C^{\mathcal{F}}(x))$

$C, D :=$	interpretation of x
$\exists R \cdot C$	$\sup_y R^{\mathcal{F}}(x, y) \underset{\circ}{\wedge} C^{\mathcal{F}}(y)$
$\forall R \cdot C$	$\inf_y R^{\mathcal{F}}(x, y) \underset{\circ}{\Rightarrow} C^{\mathcal{F}}(y)$
$(n C)$ $\text{mod}(C)$	$n \cdot C(x)$ $\text{mod}(C^{\mathcal{F}}(x))$
$w_1 C_1 + \dots + w_k C_k$	$w_1 C_1^{\mathcal{F}}(x) + \dots + w_k C_k^{\mathcal{F}}(x)$

$C, D :=$	interpretation of x
$\exists R \cdot C$	$\sup_y R^{\mathcal{F}}(x, y) \underset{\circ}{\wedge} C^{\mathcal{F}}(y)$
$\forall R \cdot C$	$\inf_y R^{\mathcal{F}}(x, y) \underset{\circ}{\Rightarrow} C^{\mathcal{F}}(y)$
$(n C)$ $\text{mod}(C)$	$n \cdot C(x)$ $\text{mod}(C^{\mathcal{F}}(x))$
$w_1 C_1 + \dots + w_k C_k$	$w_1 C_1^{\mathcal{F}}(x) + \dots + w_k C_k^{\mathcal{F}}(x)$
$C \underset{\vee}{\leq} n$	$\begin{cases} C^{\mathcal{F}}(x) & C^{\mathcal{F}}(x) \underset{\vee}{\leq} n \\ 0 & \text{otherwise} \end{cases}$

Male \sqcap Female \neq \perp



Modifier is a function that alters the membership function.

Example

Linear modifier of degree c is

$$a = \frac{c}{c + 1}$$

$$b = \frac{1}{c + 1}$$

Ontology consists of \mathcal{A} Box and \mathcal{T} Box:

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$:

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \mid \alpha \rangle$ and *role assertions* $\langle (i, j \in I) : r \in R \mid \alpha \rangle$.

Ontology consists of $\mathcal{A}Box$ and $\mathcal{T}Box$:

$\mathcal{A}Box$ (Assertion Box)

Contains *concept assertions* $\langle i \in I : p \in P \mid \alpha \rangle$ and *role assertions* $\langle (i, j \in I) : r \in R \mid \alpha \rangle$.

$\mathcal{T}Box$ (Terminology Box)

GCI axioms $\langle C \sqsubseteq D \mid \alpha \rangle$ state that “C is D at least by α ”.

Besides GCI, there are role hierarchy axioms $\langle R_1 \sqsubseteq R_2 \rangle$, transitivity axioms and definitions of inverse relations.

Fuzzy axioms

axiom	satisfied if
$\langle i : C \alpha \rangle$	$C^{\mathcal{I}}(i^{\mathcal{I}}) \geq \alpha$

Notion of a fuzzy truth

Fuzzy axioms

axiom	satisfied if
$\langle i : C \mid \alpha \rangle$	$C^{\mathcal{F}}(i^{\mathcal{F}}) \geq \alpha$
$\langle (i, j) : R \mid \alpha \rangle$	$R^{\mathcal{F}}(i^{\mathcal{F}}, j^{\mathcal{F}}) \geq \alpha$
$\langle C \sqsubseteq D \mid \alpha \rangle$	$C \overset{\circ}{\subseteq} D \geq \alpha$

Notion of a fuzzy truth

Fuzzy axioms

axiom	satisfied if
$\langle i : C \mid \alpha \rangle$	$C^{\mathcal{I}}(i^{\mathcal{I}}) \geq \alpha$
$\langle (i, j) : R \mid \alpha \rangle$	$R^{\mathcal{I}}(i^{\mathcal{I}}, j^{\mathcal{I}}) \geq \alpha$
$\langle C \sqsubseteq D \mid \alpha \rangle$	$C \overset{\circ}{\subseteq} D \geq \alpha$
$\langle R_1 \sqsubseteq R_2 \rangle$	$R_1^{\mathcal{I}} \subseteq R_2^{\mathcal{I}}$
$\langle \text{transitive } R \rangle$	$R \text{ is } \circ\text{-transitive}$

Notion of a fuzzy truth

Fuzzy axioms

axiom	satisfied if
$\langle i : C \mid \alpha \rangle$	$C^{\mathcal{F}}(i^{\mathcal{F}}) \geq \alpha$
$\langle (i, j) : R \mid \alpha \rangle$	$R^{\mathcal{F}}(i^{\mathcal{F}}, j^{\mathcal{F}}) \geq \alpha$
$\langle C \sqsubseteq D \mid \alpha \rangle$	$C \overset{\circ}{\subseteq} D \geq \alpha$
$\langle R_1 \sqsubseteq R_2 \rangle$	$R_1^{\mathcal{F}} \subseteq R_2^{\mathcal{F}}$
$\langle \text{transitive } R \rangle$	R is \circ -transitive
$\langle R_1 = R_2^{-1} \rangle$	$R_1^{\mathcal{F}} = (R_2^{\mathcal{F}})^{-1}$

Fuzzy axioms

axiom	satisfied if
$\langle i : C \mid \alpha \rangle$	$C^{\mathcal{F}}(i^{\mathcal{F}}) \geq \alpha$
$\langle (i, j) : R \mid \alpha \rangle$	$R^{\mathcal{F}}(i^{\mathcal{F}}, j^{\mathcal{F}}) \geq \alpha$
$\langle C \sqsubseteq D \mid \alpha \rangle$	$C \overset{\circ}{\subseteq} D \geq \alpha$
$\langle R_1 \sqsubseteq R_2 \rangle$	$R_1^{\mathcal{F}} \subseteq R_2^{\mathcal{F}}$
$\langle \text{transitive } R \rangle$	$R \text{ is } \circ\text{-transitive}$
$\langle R_1 = R_2^{-1} \rangle$	$R_1^{\mathcal{F}} = (R_2^{\mathcal{F}})^{-1}$

Using these definitions, the notions of *logical consequence* and *satisfiability* (of both concepts and axioms) remains the same. More on slide 217.

What can you ask the reasoner?

Best/Worst Degree Bound

What is the minimal degree of an axiom that \mathcal{K} ensures?

$$glb(\mathcal{K}, \tau) = \sup\{\alpha \mid \mathcal{K} \models \langle \tau \geq \alpha \rangle\}$$

$$wub(\mathcal{K}, \tau) = \inf\{\alpha \mid \mathcal{K} \models \langle \tau \leq \alpha \rangle\}$$

where τ is an axiom of type $\langle i : C \rangle$ or $\langle (i, j) : R \rangle$ or $\langle C \sqsubseteq D \rangle$.

What can you ask the reasoner?

Best/Worst Degree Bound

What is the minimal degree of an axiom that \mathcal{K} ensures?

$$glb(\mathcal{K}, \tau) = \sup\{\alpha \mid \mathcal{K} \models \langle \tau \geq \alpha \rangle\}$$

$$wub(\mathcal{K}, \tau) = \inf\{\alpha \mid \mathcal{K} \models \langle \tau \leq \alpha \rangle\}$$

where τ is an axiom of type $\langle i : C \rangle$ or $\langle (i, j) : R \rangle$ or $\langle C \sqsubseteq D \rangle$.

- From an empty \mathcal{K} , you cannot infer anything and therefore $glb(\mathcal{K}, \tau) = 0$ and $wub(\mathcal{K}, \tau) = 1$ (if using atomic concepts only). Only by adding new axioms into \mathcal{K} , the bounds “tighten up”.

What can you ask the reasoner?

Best/Worst Degree Bound

What is the minimal degree of an axiom that \mathcal{K} ensures?

$$glb(\mathcal{K}, \tau) = \sup\{\alpha \mid \mathcal{K} \models \langle \tau \geq \alpha \rangle\}$$

$$wub(\mathcal{K}, \tau) = \inf\{\alpha \mid \mathcal{K} \models \langle \tau \leq \alpha \rangle\}$$

where τ is an axiom of type $\langle i : C \rangle$ or $\langle (i, j) : R \rangle$ or $\langle C \sqsubseteq D \rangle$.

- From an empty \mathcal{K} , you cannot infer anything and therefore $glb(\mathcal{K}, \tau) = 0$ and $wub(\mathcal{K}, \tau) = 1$ (if using atomic concepts only). Only by adding new axioms into \mathcal{K} , the bounds “tighten up”.
- What happens if $glb(\mathcal{K}, \tau) \geq wub(\mathcal{K}, \tau)$ for some axiom τ ?

What can you ask the reasoner?

Best Satisfiability Bound

What is the maximal degree of satisfiability of C ?

$$glb(\mathcal{K}, C) = \sup_{\mathcal{F}} \sup_{x \in \Delta} \{C^{\mathcal{F}}(x) \mid \mathcal{F} \models \mathcal{K}\}.$$

What can you ask the reasoner?

Best Satisfiability Bound

What is the maximal degree of satisfiability of C ?

$$glb(\mathcal{K}, C) = \sup_{\mathcal{F}} \sup_{x \in \Delta} \{C^{\mathcal{F}}(x) \mid \mathcal{F} \models \mathcal{K}\}.$$

This is a generalization of *concept satisfiability*.

Next time we will see a reasoning algorithm for fuzzy DL. Please read [Straccia and Bobillo, 2008]:

Basic idea of the fuzzyDL solver:

Straccia, Umberto and Fernando Bobillo. **“Mixed integer programming, general concept inclusions and fuzzy description logics.”**

Mathware & Soft Computing 14, no. 3 (2008): 247-259.

Where can you find the article? Google scholar is a place to start.



Baader, F. (2003).

The Description Logic Handbook: Theory, Implementation, and Applications.

Cambridge University Press.



Bobillo, O. and Straccia, U. (2008).

fuzzydl: An expressive fuzzy description logic reasoner.

In In Proc. FUZZ-IEEE-2008. IEEE Computer Society, pages 923--930.



Straccia, U. and Bobillo, F. (2008).

Mixed integer programming, general concept inclusions and fuzzy description logics.

Mathware and Soft Computing, 14(3):247--259.