

Graph Neural Networks

Network Application Diagnostics

B2M32DSAA

Radek Mařík

Czech Technical University
Faculty of Electrical Engineering
Department of Telecommunication Engineering
Prague CZ

November 18, 2025



1 Deep Learning

- Advanced Neural Networks

2 Network Inference

- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)

- Embeddings and Neural Network Architectures



Outline

1 Deep Learning

- Advanced Neural Networks

2 Network Inference


- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)

- Embeddings and Neural Network Architectures




UNet Neural Network (CRAFT^[BLH⁺19])



Used in computer vision in segmentation.

<https://towardsdatascience.com/understanding-u-net-61276b10f360>

Generative adversarial networks (GANs) (2014)



Wasserstein GAN (2017)

<http://www.lherranz.org/2018/08/07/imagetranslation/>



Fake Image Generation (2018)




2014



2015



2016



2017



2018



Image Style Conversion - CycleGAN (2017) ^[ZPIE17]

Monet $\leftrightarrow$ Photos



Monet $\rightarrow$ photo



photo $\rightarrow$ Monet

Summer $\leftrightarrow$ Winter



summer $\rightarrow$ winter



winter $\rightarrow$ summer



Image Style Conversion Failures (2017) ^[ZPIE17]



Outline

1 Deep Learning

- Advanced Neural Networks

2 Network Inference

- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)

- Embeddings and Neural Network Architectures



Network Topology Inference ^[Kol09]

- What should constitute a vertex and an edge is determined by user-specified decisions and rules.
- Such a network graph construction lacks an element of validation.
 - if the network representation is “accurate”,
 - i.e. capturing some well-defined but unobservable relational structure.
 - What accuracy can be expected given the available measurements?
 - Are there other similar representations with about the same accuracy?
 - How is the representation robust to changes in the measurements?
 - How is the representation useful for other purposes?

Network Topology Inference Problem

- Given a set of measurements from a system of interest, e.g.
 - vertex attributes $\mathbf{x} = (x_1, \dots, x_{N_V})$
 - binary indicators $\mathbf{y} = [y_{ij}]$ of certain edges.
- and given a collection $\mathcal{G}$ of potential graphs G ,
- select an appropriate member of $\mathcal{G}$ that best captures the underlying state of the system.

Network Topology Inference ^[Kol09]

- What should constitute a vertex and an edge is determined by user-specified decisions and rules.
- Such a network graph construction lacks an element of validation.
 - if the network representation is “accurate”,
 - i.e. capturing some well-defined but unobservable relational structure.
 - What accuracy can be expected given the available measurements?
 - Are there other similar representations with about the same accuracy?
 - How is the representation robust to changes in the measurements?
 - How is the representation useful for other purposes?

Network Topology Inference Problem

- Given a set of measurements from a system of interest, e.g.
 - vertex attributes $\mathbf{x} = (x_1, \dots, x_{N_V})$
 - binary indicators $\mathbf{y} = [y_{ij}]$ of certain edges.
- and given a collection $\mathcal{G}$ of potential graphs G ,
- select an appropriate member of $\mathcal{G}$ that best captures the underlying state of the system.

Network Inference Problems ^[Kol09]

- **Link Prediction** ... inferring whether or not a pair of vertices does or does not have an edge between them
 - using measurements that include a subset of vertex pairs whose edge/non-edge status is already observed.
 - knowledge of all of the vertices.
 - the status of some of the edges/non-edges
- **Association Graph Inference** ... the relation defining edges is itself unobserved and must be inferred from measurements reflecting these characteristics.
 - no knowledge of edge status anywhere in the network graph,
 - relevant measurements at all of the vertices are assumed.
- **Tomographic Network Inference** ... the measurements are available only at vertices that are somehow at the perimeter of the network.
 - measurements at only a particular subset of vertices are known.



Outline

1 Deep Learning

- Advanced Neural Networks

2 Network Inference


- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)


- Embeddings and Neural Network Architectures



Exemplar (Viber) Environment ^[MBKK15]



Example Capture Characteristics [MBKK15]




- 138882 PCAP blocks
- 1788 transport sessions
- 2 clients
- 22 viber.com servers
- 150 peers of 2 clients
- 5660 possible concurrent sessions
- How to analyze?



Concurrent Communication Detection ^[MBKK15]

Selection of IP nodes


- *viber.com* servers → viber clients → other Viber servers
- classified based on entropy based characteristics of TCP/IP distributions



$$s(a, b) = \frac{\sum_{\forall i, j: t_a[i] - t_b[j] < R} R / (t_a[i] - t_b[j])}{\sum_{\forall i, j: t_a[i] - t_b[j] < R} 1}$$

In our experiments: $R = 50ms$, $s(a, b) > 0.001$


UDP packet sequence concurrency as a complex network ^[MBKK15]



- captures with two clients
- "*communities*" of concurrent sessions
- some clusters related to only one client
- interesting clusters consist of nodes of both clients




UDP packet sequence concurrency network component ^[MBKK15]



- restricted on one of the components
- two *Viber* clients
- 192.168.73.13
- 192.168.150.2


UDP packet sequence concurrency - packet timing ^[MBKK15]




- signals
- calls
- keep-alive packets
- direct client to client packets




Message Sending ^[MBKK15]



Voice Call [MBKK15]



Security/Privacy Assessment - Contact Picture Transfer



Outline

1 Deep Learning

- Advanced Neural Networks

2 Network Inference


- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)

- Embeddings and Neural Network Architectures





Graph Neural Network Concept



<https://www.datacamp.com/tutorial/comprehensive-introduction-graph-neural-networks-gnns-tutorial>



Graph Message Passing




<http://web.stanford.edu/class/cs224w/slides/06-GNN1.pdf>




GNN Problems


Graph Classification




Node Classification




Link Prediction




Community Detection



Graph Embedding




Graph Generation




<https://www.datacamp.com/tutorial/comprehensive-introduction-graph-neural-networks-gnns-tutorial>



Input Dataset - Facsmiles with Hieroglyphic Texts




Hieroglyph Detection



CRAFT detector (no affinities) ^[BLH⁺19]




Detection Probability




A measure that a blob is a hieroglyph


Blob Neighborhood Network




Classified Hieroglyphs, Strips and Neighborhood Edges



Classified Hieroglyphs, Strips and Neighborhood Edges



Classified Hieroglyphs, Strips and Neighborhood Edges



Outline

1 Deep Learning

- Advanced Neural Networks

2 Network Inference





- Introduction
- Network Inference Example - Viber
- Graph Neural Network (GNN)

3 Natural Language Processing (NLP)


- Embeddings and Neural Network Architectures



Embeddings - Word2vec Word Representation (Skipgram)



Recurrent Neural Network (RNN)




Used in natural language processing.

<https://www.i2tutorials.com/what-is-the-difference-between-bidirectional-rnn-and-rnn/>



Long Short-Term Memory (LSTM) Network ^[HS97]



sigmoid




tanh

pointwise
multiplicationpointwise
additionvector
concatenation

Used in natural language processing.

Sequence2Sequence Network ^[SVL14]




Used in natural language processing.

<https://www.analyticsvidhya.com/blog/2020/08/a-simple-introduction-to-sequence-to-sequence-models/>




Self and Cross Attention ^[BCB16]

The Self-Attentions



The Cross-Attentions



Used in natural language processing and computer vision.

https://www.linkedin.com/posts/damienbenveniste_

what-is-the-difference-between-self-attention-activity-7211029906166624257-m0Wn/

Transformer Network ^[VSP⁺17]

- Used in natural language processing.
- Self-Attention. . . attention applied to a single sequence (position dependencies)
- Multi-head Attention . . . several subspaces of attention
- Language models
 - ELMo . . . March 2018,
 - GPT . . . June 2018, 117Mi pars
 - BERT . . . May 2019, BERTlarge 340M pars,
 - ALBERT(base:12M, xxlarge: 235M), RoBERTa (160GB of text), DistillBERT (66 mil.), DeBERTa (2021.01, 1.5B)
 - GPT2 . . . November 2019, 1.5Bi pars, 8 milion web pages (40GB)
 - XLNet . . . January 2020, Large: 340M pars
 - GPT3 . . . July 2020, 175Bi pars
 - GPT4 . . . March 2023, ≈1.7 trillion pars




Figure 1: The Transformer - model architecture.

<https://towardsdatascience.com/transformer-neural-network-step-by-step-breakdown-of-the-beast-b3e096dc857f>

Gardiner Code to Transliteration Translation




ḥtp-dj-nsw Asjr nb Ddw nTr aA nb AbDw

Htp-dj-nsw Asjr nb Ddw nTr aA nb AbDw

An offering which the king gives (to) Osiris,
lord of Djedu, great god, lord of Abydos

Model 7 Cross Attention Visualization (2H/1B+2H/2B)





THANK YOU

THANK YOU

References I

- [BCB16] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate, 2016.
- [BLH⁺19] Youngmin Baek, Bado Lee, Dongyoon Han, Sangdo Yun, and Hwalsuk Lee. Character region awareness for text detection. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9357–9366, 2019.
- [HS97] Sepp Hochreiter and Jürgen Schmidhuber. Long Short-Term Memory. *Neural Computation*, 9(8):1735–1780, 11 1997.
- [Kol09] Eric D. Kolaczyk. *Statistical Analysis of Network Data: Methods and Models*. Springer, 2009.
- [MBKK15] Radek Mařík, Pavel Bezpalec, Jan Kučerák, and Lukáš Kencí. Revealing viber communication patterns to assess protocol vulnerability. In *2015 International Conference on Computing and Network Communications (CoCoNet). Leonia, NJ 07605: EDAS Conference Services*, pages 502–510, 2015.
- [SVL14] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks, 2014.
- [VSP⁺17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.
- [ZPIE17] Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networkss. In *Computer Vision (ICCV), 2017 IEEE International Conference on*, 2017.

