

# Introduction to C Programming

Jan Faigl

Department of Computer Science  
Faculty of Electrical Engineering  
Czech Technical University in Prague

Lecture 01

B3B36PRG – C Programming Language

## Part I

### Part 1 – Course Organization

## Overview of the Lecture

- Part 1 – Course Organization
  - Course Goals
  - Means of Achieving the Course Goals
  - Evaluation and Exam
- Part 2 – Introduction to C Programming
  - Program in C
  - Values and Variables
  - Expressions
  - Standard Input/Output
- Part 3 – Assignment HW 01

*K. N. King: chapters 1, 2, and 3*

## Course and Lecturer

### B3B36PRG – Programming in C

- Course web page <https://cw.fel.cvut.cz/wiki/courses/b3b36prg>  
<https://cw.fel.cvut.cz/wiki/courses/bab36prga>
- Submission of the homeworks – **BRUTE** Upload System  
<https://cw.felk.cvut.cz/brute> and individually during the labs for the homeworks HW08-10 with STM32F446 board (B3B36PRG) and HW8 (BAB36PRGA)
- Lecturer:


- prof. Ing. **Jan Faigl**, Ph.D.







- Department of Computer Science – <http://cs.fel.cvut.cz>
- Artificial Intelligence Center (AIC) <http://aic.fel.cvut.cz>
- Center for Robotics and Autonomous Systems (CRAS) <http://robotics.fel.cvut.cz>
- Computational Robotics Laboratory (ComRob) <http://comrob.fel.cvut.cz>


Course Goals	Means of Achieving the Course Goals	Evaluation and Exam
<h2>Course Goals</h2> <ul style="list-style-type: none"> <li>■ <b>Master</b> (yourself) programming skills</li> <li>■ <b>Acquire</b> knowledge of C programming language</li> <li>■ <b>Acquire experience</b> of C programming to use it efficiently</li> <li>■ <b>Gain experience</b> to read, write, and understand small C programs</li> <li>■ <b>Acquire</b> programming habits to write <ul style="list-style-type: none"> <li>■ easy to read and understandable source codes</li> <li>■ reusable programs</li> </ul> </li> <li>■ <b>Experience</b> programming with <ul style="list-style-type: none"> <li>■ Workstation/desktop computers – using services of operating system <i>E.g., system calls, read/write files, input and outputs</i></li> <li>■ Multithreading applications</li> <li>■ Embedded applications – STM32F446 Nuc1eo (B3B36PRG)</li> </ul> </li> </ul>		
		<p><i>Labs, homeworks, exam</i></p> <p><i>Your own experience!</i></p>
Jan Faigl, 2020	B3B36PRG – Lecture 01: Introduction to C Programming	6 / 82

Course Goals	Means of Achieving the Course Goals	Evaluation and Exam
<h2>Course Organization and Evaluation</h2> <ul style="list-style-type: none"> <li>■ B3B36PRG – Programming in C</li> <li>■ BAB36PRGA – Programming in C</li> <li>■ Extent of teaching: 2(lec)+2(lab)+5(hw)</li> <li>■ Completion: Z,ZK</li> <li>■ Credits: 6</li> </ul> <hr/> <ul style="list-style-type: none"> <li>■ Ongoing work during the semester <ul style="list-style-type: none"> <li>■ Homeworks <i>mandatory, optional, and bonus parts</i></li> <li>■ Semestral project – an application for a workstation (and STM32F446 – B3B36PRG)</li> </ul> </li> <li>■ Exam test and implementation exam <i>Be able to independently work with the computer in the lab (class room)</i></li> </ul> <hr/> <ul style="list-style-type: none"> <li>■ Attendance to labs, submission of homeworks, and semestral project</li> </ul>		
		<i>Z – ungraded assessment, ZK – exam</i>
Jan Faigl, 2020	B3B36PRG – Lecture 01: Introduction to C Programming	7 / 82


Course Goals	Means of Achieving the Course Goals	Evaluation and Exam
<h2>Resources and Literature</h2> <ul style="list-style-type: none"> <li>■ <b>Textbook</b> <p><i>„C Programming: A Modern Approach“ (King, 2008)</i></p> <p> C Programming: A Modern Approach, 2nd Edition, K. N. King, W. W. Norton &amp; Company, 2008, ISBN 860-1406428577</p> <p><i>The main course textbook</i></p> </li> <li>■ Lectures – support for the textbook, slides, comments, and <b>your notes</b> <i>Demonstration source codes are provided as a part of the lecture materials!</i></li> <li>■ Laboratory exercises – gain practical skills by doing homeworks (yourself)</li> </ul>		
Jan Faigl, 2020	B3B36PRG – Lecture 01: Introduction to C Programming	9 / 82


Course Goals	Means of Achieving the Course Goals	Evaluation and Exam
<h2>Further Books</h2> <ul style="list-style-type: none"> <li>■  Programming in C, 4th Edition, Stephen G. Kochan, Addison-Wesley, 2014, ISBN 978-0321776419</li> <li>■  21st Century C: C Tips from the New School, Ben Klemens, O'Reilly Media, 2012, ISBN 978-1449327149</li> <li>■  The C Programming Language, 2nd Edition (ANSI C), Brian W. Kernighan, Dennis M. Ritchie, Prentice Hall, 1988 (1st edition – 1978)</li> <li>■  Advanced Programming in the UNIX Environment, 3rd edition, W. Richard Stevens, Stephen A. Rago Addison-Wesley, 2013, ISBN 978-0-321-63773-4</li> </ul>		
Jan Faigl, 2020	B3B36PRG – Lecture 01: Introduction to C Programming	10 / 82

## Further Resources

 **The C++ Programming Language, 4th Edition (C++11)** ,  
*Bjarne Stroustrup*, Addison-Wesley, 2013, ISBN 978-0321563842



 **Introduction to Algorithms, 3rd Edition**, *Cormen, Leiserson, Rivest, and Stein*, The MIT Press, 2009, ISBN 978-0262033848



 **Algorithms, 4th Edition** , *Robert Sedgewick, Kevin Wayne*, Addison-Wesley, 2011, ISBN 978-0321573513



## Teachers

■ Ing. Jan Bayer



■ Bc. Martin Zoula



■ Bc. Miroslav Tržil



■ Bc. Jiří Kubík



■ Ing. Petr Čížek



■ Bc. Jindřiška Deckerová



■ Bc. David Valouch



■ Bc. Jakub Sláma



■ Ing. Rudolf J. Szadkowski  
Lectures 1 and 2



■ Ing. Petr Váňa  
Former author of the automated evaluation  
in BRUTE Upload System



## Lectures – Spring Semester Academic Year 2019/2020

■ Schedule for the academic year 2019/2020

<http://www.fel.cvut.cz/en/education/calendar.html>

■ Lectures:

■ Dejvice, Lecture Hall No. T2:D3-209, Tuesday, 14:30-16:00

■ 14 teaching weeks

*12+1 lectures (the last lecture for exam test?)*

■ Thursday 9.4.2020 – classes as on Friday (even calendar week)

■ Tuesday 5.5.2020 – classes as on Friday (odd calendar week)

## Communicating Any Issues Related to the Course

■ Ask the lab teacher or the lecturer

■ Use e-mail for communication

■ Use your **faculty e-mail**

■ **Put PRG or B3B36PRG or BAB36PRGA to the subject of your message**

■ Send copy (Cc) to lecturer/teacher

## Computers and Development Tools

- Network boot with home directories (NFS v4)  
*Data transfer and file synchronizations – ownCloud, SSH, FTP, USB*  
<https://gcc.gnu.org> or <http://clang.llvm.org>
- Compilers **gcc** or **clang**
- Project building **make** (GNU make)  
*Examples of usage on lectures and labs*  
<https://atom.io/>, <http://www.sublimetext.com/>  
<http://www.root.cz/clanky/textovy-editor-vim-jako-ide>
- Text editor – gedit, **atom**, **sublime**, **vim**
- C/C++ development environments – **WARNING: Do Not Use An IDE**  
<http://c.learnthecodethehardway.org/book/ex0.html>  
*At least at the beginning, to become familiar with syntax*
  - Debugging – code **gdb**, **gdbgui**, **cgdb**, **ddd**
  - Visual Studio Code** – code
  - CLion** – <https://www.jetbrains.com/clion>
  - Code::Blocks, CodeLite  
<http://www.codeblocks.org>, <http://codelite.org>
  - NetBeans (C/C++), **Eclipse-CDT**
- Embedded development for the Nucleo** (B3B36PRG only)
  - ARMmbed** – <https://developer.mbed.org/platforms/ST-Nucleo-F446RE>
  - System Workbench for STM32** (based on Eclipse)
  - Direct cross-compiling** using makefiles

## Homeworks - B3B36PRG (KyR)

- 10+1 homeworks - seven for the workstation and three for the Nucleo platform
- 1. HW 00 – **Testing** (0 points) <https://cw.fel.cvut.cz/wiki/courses/b3b36prg/hw/start>
- 2. HW 01 – **ASCII Art** (2 points)
- 3. HW 02 – **Prime Factorization** (2 points + 4 points optional)  
**Coding style penalization – up to -100% from the gain points**
- 4. HW 03 – **Caesar Cipher** (2 points + 2 points optional) **Coding style penalization**
- 5. HW 04 – **Text Search** (2 points + 3 points optional)
- 6. HW 05 – **Matrix Calculator** (2 points + 2 points optional + 5 points bonus)
- 7. HW 06 – **Circular Buffer** (2 points + 2 points optional)
- 8. HW 07 – **Linked List Queue with Priorities** (2 pts + 3 pts optional) **Coding style penalization!**
- 9. HW 08 – **Nucleo – LED and Button** (2 points)
- 10. HW 09 – **Nucleo – Single Byte Serial Communication** (2 points) **Coding style penalization!**
- 11. HW 10 – **Nucleo – Computation and Communication**: (2 points) **Coding style penalization!**
  - All homeworks must be submitted to award an ungraded assessment  
**Late submission is penalized!**

## Services – Academic Network, FEE, CTU

- <http://www.fel.cvut.cz/cz/user-info/index.html>
- Cloud storage ownCloud – <https://owncloud.cesnet.cz>
- Sending large files – <https://filesender.cesnet.cz>
- Schedule, deadlines – FEL Portal, <https://portal.fel.cvut.cz>
- FEL Google Account** – access to Google Apps for Education  
See <http://google-apps.fel.cvut.cz/>
- Gitlab FEL – <https://gitlab.fel.cvut.cz/>
- Information resources (IEEE Xplore, ACM, Science Direct, Springer Link)  
<https://dialog.cvut.cz>
- Academic and campus software license  
<https://download.cvut.cz>
- National Super Computing Grid Infrastructure – MetaCentrum  
<http://www.metacentrum.cz/cs/index.html>

## Homeworks - BAB36PRGA (Bio)

- 8+1 homeworks - all for the workstation  
<https://cw.fel.cvut.cz/wiki/courses/bab36prga/hw/start>
- 1. HW 0 – **Testing** (0 points)
- 2. HW 1 – **ASCII Art** (2 points)
- 3. HW 2 – **Prime Factorization** (2 points + 4 points optional)  
**Coding style penalization – up to -100% from the gain points**
- 4. HW 3 – **Caesar Cipher** (2 points + 2 points optional) **Coding style penalization**
- 5. HW 4 – **Text Search** (2 points + 3 points optional)
- 6. HW 5 – **Matrix Calculator** (2 points + 4 points optional + 5 points bonus)
- 7. HW 6 – **Circular Buffer** (2 points + 2 points optional)
- 8. HW 7 – **Linked List Queue with Priorities** (2 pts + 2 pts optional) **Coding style penalization!**
- 9. HW 8 – **Interactive application with Inter Process Communication (ICP)** (3 points)  
**Coding style penalization!**
  - All homeworks must be submitted to award an ungraded assessment  
**Late submission is penalized!**
  - Optional assignments to gain points

## Semester Project (B3B36PRG)

- A combination of application for workstation (multi-threading / communication / interaction ) and program for the Nucleo STM32F446
- Computation on the embedded platform via control application
- Mandatory task can be awarded up to **20 points**
- Bonus part can be awarded for additional **10 points**
  - Up to 30 points in the total for the semestral project
  - E.g., distributed computation using several Nucleo STM32F446 boards
- **Minimum required points: 15!**

Deadline – best before 13.5.2020  
 Further updates and additional points possible!  
 Deadline – latest 17.5.2020

## Course Evaluation (B3B36PRG)

Points	Maximum Points	Required Points	Minimum Points
Homeworks	40	20	
Semester Project	30	15	
Exam test	20		<b>10</b>
Implementation exam	20		<b>10</b>
<b>Total</b>	<b>110 points</b>	<b>35 points is F!</b>	

- **20 points** from the homeworks and 15 points from the semestral project are required for awarding ungraded assessment
- The course can be passed with **ungraded assessment** and **exam**
- **All homeworks must be submitted and they have to pass the mandatory assessment**

## Semester Project (BAB36PRGA)

- An application for workstation (multi-threading / communication / interaction ) and computational program (a module simulating behaviour of Nucleo STM32F446)
- Mandatory task can be awarded up to **12 points**
- Extra part can be awarded for additional **8 points**
  - Up to 20 points in the total for the semestral project
  - E.g., interactive selection of the image size, animation, saving images, window refreshing.
- **Minimum required points: 10!**

Deadline – best before 13.5.2020  
 Further updates and additional points possible!  
 Deadline – latest 17.5.2020

*Except the communication, the applications can be almost identical with the computational module (communication via pipe-based IPC) and STM32F446 Nucleo board (communication via serial line).*

## Course Evaluation (BAB36PRGA)

Points	Maximum Points	Required Points	Minimum Points
Homeworks	40	<b>25</b>	
Semester Project	20	10	
Exam test	20		<b>10</b>
Implementation exam	20		<b>10</b>
<b>Total</b>	<b>100 points</b>	<b>35 points is F!</b>	

- **25 points** from the homeworks and 10 points from the semestral project are required for awarding ungraded assessment *There is a strong recommendation for optional assignments*
- **Mandatory assignments are for 17 points, optional for additional 18 points**
- The course can be passed with **ungraded assessment** and **exam**
- **All homeworks must be submitted and they have to pass the mandatory assessment**

## Grading Scale

Grade	Points	Mark	Evaluation
A	≥ 90	1	Excellent
B	80–89	1,5	Very Good
C	70–79	2	Good
D	60–69	2,5	Satisfactory
E	50–59	3	Sufficient
F	<50	4	Fail

- All homeworks passed the mandatory assessment and some of them with optional parts (for additional 10 points) Gain around 30 points out of 40 (50) points
- Semestral project for up 30 points In an average, around 10-20 points or 25 with the bonus part
- Exam: test (15 points) and implementation (10 points) Realistic (average good) expected scoring 30 + 20 + 15 + 10
- Around 75 points (C – Good)
- Optional and bonus tasks are needed for around 95 points

## Part II

### Part 2 – Introduction to C Programming

## Overview of the Lectures

1. Course information, Introduction to C programming *K. N. King: chapters 1, 2, and 3*
2. Writing your program in C, control structures (loops), expressions *K. N. King: chapters 4, 5, 6, and 20*
3. Data types, arrays, pointer, memory storage classes, function call *K. N. King: chapters 7, 8, 9, 10, 11, and 18*
4. Data types: arrays, strings, and pointers *K. N. King: chapters 8, 11, 12, 13, and 17*
5. Data types: Struct, Union, Enum, Bit fields. Preprocessor and Large Programs *K. N. King: chapters 10, 14, 15, 16, and 20*
6. Input/Output – reading/writing from/to files and other communication channels, Standard C library – selected functions *K. N. King: chapters 21, 22, 23, 24, 26, and 27*
7. Parallel and multi-thread programming – methods and synchronizations primitives
8. Multi-thread application models, POSIX threads and C11 threads
9. Examples - C programming language wrap up
10. *ANSI C, C99, C11 and differences between C and C++*. Introduction to C++.
11. Quick introduction to C++
12. *C++ examples*
13. *Exam test or Reserve*

All supporting materials for the lectures are available at  
<https://cw.fel.cvut.cz/b192/courses/b3b36prg/lectures/start>  
 Read them before the lecture!

## C Programming Language

- Low-level programming language
- System programming language (operating system) *Language for (embedded) systems — MCU, cross-compilation*
- A user (programmer) can do almost everything *Initialization of the variables, release of the dynamically allocated memory, etc.*
- Very close to the hardware resources of the computer *Direct calls of OS services, direct access to registers and ports*
- Dealing with memory is crucial for correct behaviour of the program *One of the goals of the PRG course is to acquire fundamental principles that can be further generalized for other programming languages. The C programming language provides great opportunity to become familiar with the memory model and key elements for writing efficient programs.*

**It is highly recommended to have compilation of your program fully under control**

*It may look difficult at the beginning, but it is relatively easy and straightforward. Therefore, we highly recommend to use fundamental tools for your program compilation. After you acquire basic skills, you can profit from them also in more complex development environments.*

## Writing Your C Program

- Source code of the C program is written in **text files**
  - Header files** usually with the suffix **.h**
  - Sources files** usually named with the suffix **.c**
- Header and source files together with **declaration** and **definition** (of functions) support
  - Organization** of sources into several files (modules) and libraries
  - Modularity** – Header file declares a visible interface to others
    - A description (list) of functions and their arguments without particular implementation*
  - Reusability**
    - Only the “interface” declared in the header files is need to use functions from available binary libraries

## Writing Identifiers in C

- Identifiers are names of variables (custom types and functions)
  - Types and functions, viz further lectures*
- Rules for the identifiers
  - Characters a–z, A–Z, 0–9 a \_
  - The first character is not a numeral
  - Case sensitive
  - Length of the identifier is not limited
    - First 31 characters are significant – depends on the implementation / compiler*
- Keywords<sub>32</sub>
  - auto break case char const continue default do double else enum extern float for goto if int long register return short signed sizeof static struct switch typedef union unsigned void volatile while**

C99 introduces, e.g., `inline`, `restrict`, `_Bool`, `_Complex`, `_Imaginary`  
 C11 further adds, e.g., `_Alignas`, `_Alignof`, `_Atomic`, `_Generic`, `_Static_assert`, `_Thread_local`

C98

- Escape sequences for writing special symbols
  - `\o`, `\oo`, where o is an octal numeral
  - `\xh`, `\xhh`, where h is a hexadecimal numeral

```
1 int i = 'a';
2 int h = 0x01;
3 int o = 0141;
4
5 printf("i: %i h: %i o: %i c: %c\n", i, h, o, i);
6 printf("oct: \141 hex: \x61\n");
```

*E.g., \141, \x61 lec01/esqdh.c*

- `\0` – character reserved for the end of the text string (null character)

## Simple C Program

```
1 #include <stdio.h>
2
3 int main(void)
4 {
5     printf("I like B3B36PRG!\n");
6
7     return 0;
8 }
```

*lec01/program.c*

- Source files are compiled by the compiler to the so-called **object files** usually with the suffix **.o**
  - Object code contains relative addresses and function calls or just references to function without known implementations.*
- The final executable program is created from the object files by the **linker**



### Program Compilation and Execution

- Source file program.c is compiled into runnable form by the compiler, e.g., clang or gcc

```
clang program.c
```

- There is a new file a.out that can be executed, e.g.,  
./a.out  
*Alternatively the program can be run only by a.out in the case the actual working directory is set in the search path of executable files*

- The program prints the argument of the function printf()  
./a.out  
I like B3B36PRG!

- If you prefer to run the program just by a.out instead of ./a.out you need to add your actual working directory to the search paths defined by the environment variable PATH

```
export PATH="$PATH:pwd"
```

*Notice, this is not recommended, because of potentially many working directories*

- The command pwd prints the actual working directory, see man pwd

### Structure of the Source Code – Commented Example

- Commented source file program.c

```
1 /* Comment is inside the markers (two characters)
2    and it can be split to multiple lines */
3 // In C99 - you can use single line comment
4 #include <stdio.h> /* The #include direct causes to include header file
5    stdio.h from the C standard library */
6
7 int main(void) // simplified declaration
8 {             // of the main function
9     printf("I like B3B36PRG!\n"); /* calling printf() function from the
10    stdio.h library to print string to the standard output. \n denotes
11    a new line */
12     return 0; /* termination of the function. Return value 0 to the
13    operating system */
14 }
```

### Program Building: Compiling and Linking

- The previous example combines three particular steps of the program building in a single call of the command (clang or gcc)
- The particular steps can be performed individually

- Text preprocessing by the preprocessor, which utilizes its own macro language (commands with the prefix #)  
*All referenced header files are included into a single source file*

- Compilation of the source file into the object file  
*Names of the object files usually have the suffix .o*


```
clang -c program.c -o program.o
```

*The command combines preprocessor and compiler*

- Executable file is linked from the particular object files and referenced libraries by the linker (linking), e.g.,  
clang program.o -o program

### Compilation and Linking Programs

- Program development is editing of the source code (files with suffixes .c and .h) *readable*
- Compilation of the particular source files (.c) into object files (.o or .obj) *Machine readable*
- Linking the compiled files into executable binary file
- Execution and debugging of the application and repeated editing of the source code





## Steps of Compiling and Linking

- **Preprocessor** – allows to define macros and adjust compilation the particular environment  
*The output is text (“source”) file.*
- **Compiler** – Translates source (text) file into machine readable form  
*Native (machine) code of the platform, bytecode, or assembler alternatively*
- **Linker** – links the final application from the object files  
*Under OS, it can still reference library functions (dynamic libraries linked during the program execution), it can also contain OS calls (libraries).*
- Particular steps **preprocessor**, **compiler**, and **linker** are usually implemented by a “single” program that is called with appropriate arguments  
*E.g., clang or gcc*

## Functions, Modules, and Compiling and Linking

- Function is the fundamental building block of the **modular** programming language  
*Modular program is composed of several modules/source files*
- **Function definition** consists of the
  - **Function header**
  - **Function body**  
*Definition is the function implementation.*
- **Function prototype (declaration)** is the function header to provide information how the function can be called  
*It allows to use the function prior its definition, i.e., it allows to compile the code without the function implementation, which may be located in other place of the source code, or in other module.*
- **Declaration** is the **function header** and it has the form  
`type function_name(arguments);`

## Compilers of C Program Language

- In PRG, we mostly use compilers from the families of compilers:
  - **gcc** – GNU Compiler Collection  
<https://gcc.gnu.org>
  - **clang** – C language family frontend for LLVM  
<http://clang.llvm.org>
- Under Win, two derived environments can be utilized: **cygwin** <https://www.cygwin.com/> or **MinGW** <http://www.mingw.org/>
- Basic usage (flags and arguments) are identical for both compilers  
*clang is compatible with gcc*
- Example
  - **compile:** `gcc -c main.c -o main.o`
  - **link:** `gcc main.o -o main`

## Functions in C

- Function definition inside other function is not allowed in C.
- Function names can be exported to other modules  
**Module is an independent file (compiled independently)**
- Function are implicitly declared as **extern**, i.e., visible
- Using the **static** specifier, the visibility of the function can be limited to the particular module  
**Local module function**
- Function arguments are **local variables** initialized by the values passed to the function  
*Arguments are passed by value (call by value)*
- **C allows recursions** – local variables are automatically allocated at the stack  
*Further details about storage classes in next lectures.*
- Arguments of the function are not mandatory – void arguments  
`fnc(void)`
- The return type of the function can be **void**, i.e., a function without return value –  
`void fnc(void);`

### Example of Program / Module

```

1 #include <stdio.h> /* header file */
2 #define NUMBER 5 /* symbolic constant */
3
4 int compute(int a); /* function header/prototype */
5
6 int main(int argc, char *argv[])
7 { /* main function */
8     int v = 10; /* variable declaration */
9     int r;
10    r = compute(v); /* function call */
11    return 0; /* termination of the main function */
12 }
13
14 int compute(int a)
15 { /* definition of the function */
16     int b = 10 + a; /* function body */
17     return b; /* function return value */
18 }

```

### Arguments of the main() Function

- During the program execution, the OS passes to the program the number of arguments (`argc`) and the arguments (`argv`)
  - The first argument is the name of the program

*In the case we are using OS*

```

1 int main(int argc, char *argv[])
2 {
3     int v;
4     v = 10;
5     v = v + 1;
6     return argc;
7 }

```

lec01/var.c

- The program is terminated by the `return` in the `main()` function
- The returned value is passed back to the OS and it can be further use, e.g., to control the program execution.

### Program Starting Point – main()

- Each executable program must contain a single definition of the function and that function must be the `main()`

- The `main()` function is the starting point of the program with two basic forms
  1. Full variant for programs running under an Operating System (OS)

```

int main(int argc, char *argv[])
{
    ...
}

```

2. For embedded systems without OS

```

int main(void)
{
    ...
}

```

### Example of Compilation and Program Execution

- Building the program by the `clang` compiler – it automatically joins the compilation and linking of the program to the file `a.out`

```
clang var.c
```
- The output file can be specified, e.g., program file `var`

```
clang var.c -o var
```
- Then, the program can be executed

```
./var
```
- The compilation and execution can be joined to a single command

```
clang var.c -o var; ./var
```
- The execution can be conditioned to successful compilation

```
clang var.c -o var && ./var
```

*Programs return value — 0 means OK*

*Logical operator && depends on the command interpret, e.g., sh, bash, zsh*

### Example – Program Execution under Shell

- The return value of the program is stored in the variable `$?`
- Example of the program execution with different number of arguments

`sh, bash, zsh`

```
./var

./var; echo $?
1

./var 1 2 3; echo $?
4

./var a; echo $?
2
```

### Example – Compilation of the Source Code to Assembler

- Using the `-S` flag, the source code can be compiled to Assembler  
`clang -S var.c -o var.s`

```
1  .file "var.c"
2  .text
3  .globl main
4  .align 16, 0x90
5  .type main,@function
6  main:
7  # @main
8  .cfi_startproc
9  # BB#0:
10 pushq %rbp
11 .Ltmp2:
12 .cfi_def_cfa_offset 16
13 .Ltmp3:
14 .cfi_offset %rbp, -16
15 movq %rsp, %rbp
16 .Ltmp4:
17 .cfi_def_cfa_register %rbp
18 movl $0, -4(%rbp)
19 movl %edi, -8(%rbp)
19 movq %rsi, -16(%rbp)
20 movl $10, -20(%rbp)
21 movl -20(%rbp), %edi
22 addl $1, %edi
23 movl %edi, -20(%rbp)
24 movl -8(%rbp), %eax
25 popq %rbp
26 ret
27 .Ltmp5:
28 .size main, .Ltmp5-main
29 .cfi_endproc
30
31
32 .ident "FreeBSD clang version 3.4.1 (
33 tags/RELEASE_34/dot1-final 208032)
20140512"
33 .section ".note.GNU-stack","",
@progbits
```

### Example – Processing the Source Code by Preprocessor

- Using the `-E` flag, we can perform only the preprocessor step  
`gcc -E var.c`

Alternatively `clang -E var.c`

```
1 # 1 "var.c"
2 # 1 "<built-in>"
3 # 1 "<command-line>"
4 # 1 "var.c"
5 int main(int argc, char **argv) {
6     int v;
7     v = 10;
8     v = v + 1;
9     return argc;
10 }
```

`lec01/var.c`

### Example – Compilation to Object File

- The source file is compiled to the object file  
`clang -c var.c -o var.o`

```
% clang -c var.c -o var.o
% file var.o
var.o: ELF 64-bit LSB relocatable, x86-64, version 1 (FreeBSD), not
stripped
```

- **Linking** the object file(s) provides the executable file  
`clang var.o -o var`

```
% clang var.o -o var
% file var
var: ELF 64-bit LSB executable, x86-64, version 1 (FreeBSD),
dynamically linked (uses shared libs), for FreeBSD 10.1 (1001504)
, not stripped
```

*dynamically linked  
not stripped*

### Example – Executable File under OS 1/2

- By default, executable files are “tied” to the C library and OS services
- The dependencies can be shown by `ldd var`  

```
ldd var                                ldd – list dynamic object dependencies
var:
    libc.so.7 => /lib/libc.so.7 (0x2c41d000)
```
- The so-called static linking can be enabled by the `-static`  

```
clang -static var.o -o var
% ldd var
% file var
var: ELF 64-bit LSB executable, x86-64, version 1 (FreeBSD),
    statically linked, for FreeBSD 10.1 (1001504), not stripped
% ldd var
ldd: var: not a dynamic ELF executable
```

*Check the size of the created binary files!*

### Writing Values of the Numeric Data Types – Literals

- Values of the data types are called **literals**
- C has 6 type of constants (literals)
  - Integer
    - Rational  
*We cannot simply write irrational numbers*
  - Characters
  - Text strings
  - Enumerated  
*Enum*
  - Symbolic – `#define NUMBER 10`  
*Preprocessor*

### Example – Executable File under OS 2/2

- The compiled program (object file) contains symbolic names (by default)  
*E.g., usable for debugging.*  

```
clang var.c -o var
wc -c var
    7240 var
```

*wc – word, line, character, and byte count  
-c – byte count*
- Symbols can be removed by the tool (program) **strip**  

```
strip var
wc -c var
    4888 var
```

*Alternatively, you can show size of the file by the command `ls -l`*

### Integer Literals

- Integer values are stored as one of the integer type (keywords): `int`, `long`, `short`, `char` and their `signed` and `unsigned` variants  
*Further integer data types are possible*
- Integer values (literals)
 

■ Decimal	123 450932	
■ Hexadecimal	0x12 0xFAFF	(starts with <code>0x</code> or <code>0X</code> )
■ Octal	0123 0567	(starts with <code>0</code> )
■ <code>unsigned</code>	12345U	(suffix <code>U</code> or <code>u</code> )
■ <code>long</code>	12345L	(suffix <code>L</code> or <code>l</code> )
■ <code>unsigned long</code>	12345ul	(suffix <code>UL</code> or <code>ul</code> )
■ <code>long long</code>	12345LL	(suffix <code>LL</code> or <code>ll</code> )
- Without suffix, the literal is of the type `int`

# Literals of Rational Numbers

- Rational numbers can be written
  - with floating point – 13.1
  - or with mantissa and exponent – 31.4e-3 or 31.4E-3

*Scientific notation*
- Floating point numeric types depends on the implementation, but they usually follow IEEE-754-1985  
*float, double*
- Data types of the rational literals:
  - double – by default, if not explicitly specified to be another type
  - float – suffix F or f

*float f = 10f;*

  - long double – suffix L or l

*long double ld = 10l;*

# Character Literals

- Format – single (or multiple) character in apostrophe  
*'A', 'B' or '\n'*
- Value of the single character literal is the code of the character  
*'0' ~ 48, 'A' ~ 65*  
*Value of character out of ASCII (greater than 127) depends on the compiler.*
- Type of the character constant (literal)
  - character constant is the int type


# String literals

- Format – a sequence of character and control characters (escape sequences) enclosed in quotation (citation) marks

"This is a string constant with the end of line character \n"

- String constants separated by white spaces are joined to single constant, e.g.,  
"String literal" "with the end of the line character\n"  
is concatenate into  
"String literal with end of the line character\n"

- Type
  - String literal is stored in the array of the type char terminated by the null character '\0'



*The size of the array must be about 1 item longer to store \0!*  
*More about text strings in the following lectures and labs*

# Constants of the Enumerated Type

- By default, values of the enumerated type starts from 0 and each other item increase the value about one, values can be explicitly prescribed

```
enum {
    SPADES,
    CLUBS,
    HEARTS,
    DIAMONDS
};

enum {
    SPADES = 10,
    CLUBS, /* the value is 11 */
    HEARTS = 15,
    DIAMONDS = 13
};
```

*The enumeration values are usually written in uppercase.*

- Type – enumerated constant is the int type
  - Value of the enumerated literal can be used in loops

```
enum { SPADES = 0, CLUBS, HEARTS, DIAMONDS, NUM_COLORS };
for (int i = SPADES; i < NUM_COLORS; ++i) {
    ...
}
```

## Symbolic Constant – #define

- Format – the constant is established by the preprocessor command `#define`
  - It is macro command without argument
  - Each `#define` must be on a new line

```
#define SCORE 1
```

*Usually written in uppercase*

- Symbolic constants can express constant expressions

```
#define MAX_1 ((10*6) - 3)
```

- Symbolic constants can be nested

```
#define MAX_2 (MAX_1 + 1)
```

- Preprocessor performs the text replacement of the define constant by its value**

```
#define MAX_2 (MAX_1 + 1)
```

*It is highly recommended to use brackets to ensure correct evaluation of the expression, e.g., the symbolic constant `5*MAX_1` with the outer brackets is `5*((10*6) - 3)=285` vs `5*(10*6) - 3=297`.*

## Example: Sum of Two Values

```
1 #include <stdio.h>
2
3 int main(void)
4 {
5     int sum; // definition of local variable of the int type
6
7     sum = 100 + 43; /* set value of the expression to sum */
8     printf("The sum of 100 and 43 is %i\n", sum);
9     /* %i formatting command to print integer number */
10    return 0;
11 }
```

- The variable `sum` of the type `int` represents an integer number. Its value is stored in the memory
- `sum` is selected symbolic name of the memory location, where the integer value (type `int`) is stored

## Variable with a constant value modifier (keyword) (`const`)

- Using the keyword `const`, a variable can be marked as constant  
*Compiler checks assignment and do not allow to set a new value to the variable.*
- A constant value can be defined as follows  

```
const float pi = 3.14159265;
```
- In contrast to the symbolic constant  

```
#define PI 3.14159265
```
- Constant values have type, and thus it supports **type checking**

## Example of Sum of Two Variables

```
1 #include <stdio.h>
2
3 int main(void)
4 {
5     int var1;
6     int var2 = 10; /* inicialization of the variable */
7     int sum;
8
9     var1 = 13;
10
11    sum = var1 + var2;
12
13    printf("The sum of %i and %i is %i\n", var1, var2, sum);
14
15    return 0;
16 }
```

- Variables `var1`, `var2` and `sum` represent three different locations in the memory (allocated automatically), where three integer values are stored

## Variable Declaration

- The variable declaration has general form **declaration-specifiers declarators;**
- Declaration specifiers are:
  - **Storage classes:** at most one of the `auto`, `static`, `extern`, `register`
  - **Type quantifiers:** `const`, `volatile`, `restrict`

*None or more type quantifiers are allowed*
  - **Type specifiers:** `void`, `char`, `short`, `int`, `long`, `float`, `double`, `signed`, `unsigned`.  
In addition, `struct` and `union` type specifiers can be used. Finally, own types defined by `typedef` can be used as well.
 


*Detailed description in further lectures.*

## Assignment, Variables, and Memory – Visualization unsigned char

```

1 unsigned char var1;
2 unsigned char var2;
3 unsigned char sum;
4
5 var1 = 13;
6 var2 = 10;
7
8 sum = var1 + var2;
```

- Each variable allocate 1 byte
- Content of the memory is not defined after allocation
- Name of the variable “references” to the particular memory location
- Value of the variable is the content of the memory location




## Assignment, Variables, and Memory – Visualization int

```

1 int var1;
2 int var2;
3 int sum;
4
5 // 00 00 00 13
6 var1 = 13;
7
8 // x00 x00 x01 xF4
9 var2 = 500;
10
11 sum = var1 + var2;
```

- Variables of the `int` types allocate 4 bytes
 

*Size can be find out by the operator `sizeof(int)`*
- Memory content is not defined after the definition of the variable to the memory



500 (dec) is 0x01F4 (hex)  
 513 (dec) is 0x0201 (hex)

*For Intel x86 and x86-64 architectures, the values (of multi-byte types) are stored in the little-endian order.*

## Expressions

- **Expression** prescribes calculation value of some given input
- Expression is composed of **operands**, **operators**, and **brackets**
- Expression can be formed of
  - literals
  - variables
  - constants
  - unary and binary operators
  - function calling
  - brackets
- The order of operation evaluation is prescribed by the operator **precedence** and **associativity**.

### Example

```

10 + x * y // order of the evaluation 10 + (x * y)
10 + x + y // order of the evaluation (10 + x) + y
```

*\* has higher priority than +  
 + is associative from the left-to-right*



# Operators

- Operators are selected characters (or a sequences of characters) dedicated for writing expressions
- Five types of **binary operators** can be distinguished
  - Arithmetic** operators – additive (addition/subtraction) and multiplicative (multiplication/division)
  - Relational** operators – comparison of values (less than, greater than, ...)
  - Logical** operators – logical **AND** and **OR**
  - Bitwise** operators – bitwise **AND**, **OR**, **XOR**, bitwise shift (left, right)
  - Assignment operator** = – a variables (l-value) is on its left side
- Unary operators
  - Indicating positive/negative value: + and -
 

*Operator – modifies the sign of the expression*
  - Modifying a variable : ++ and --
  - Logical negation: !
  - Bitwise negation: ~
- Ternary operator – conditional expression ? :

# Variables, Assignment Operator, and Assignment Statement

- Variables are defined by the type and name
  - Name of the variable are in lowercase
  - Multi-word names can be written with underscore \_ *Or we can use CamelCase*
  - Each variable is defined at new line
 

```
int n;
int number_of_items;
int numberOfItems;
```
- Assignment is setting the value to the variable, i.e., the value is stored at the memory location referenced by the variable name
- Assignment operator
 
$$\langle \text{l-value} \rangle = \langle \text{expression} \rangle$$

*Expression is literal, variable, function calling, ...*

  - The side is the so-called **l-value – location-value, left-value**

*It must represent a memory location where the value can be stored.*
  - Assignment is an expression and we can use it everywhere it is allowed to use the expression of the particular type.
- Assignment statement is the assignment operator = and ;

# Basic Arithmetic Expressions

- For an operator of the numeric types **int** and **double**, the following operators are defined
 

*Also for char, short, and float numeric types.*

  - Unary operator for changing the sign -
  - Binary addition + and subtraction -
  - Binary multiplication \* and division /
- For integer operator, there is also
  - Binary module (integer remainder) %
- If both operands are of the same type, the results of the arithmetic operation is the same type
- In a case of combined data types **int** and **double**, the data type **int** is converted to **double** and the results is of the **double** type.
 

*Implicit type conversion*

# Example – Arithmetic Operators 1/2

```

1  int a = 10;
2  int b = 3;
3  int c = 4;
4  int d = 5;
5  int result;
6
7  result = a - b; // subtraction
8  printf("a - b = %i\n", result);
9
10 result = a * b; // multiplication
11 printf("a * b = %i\n", result);
12
13 result = a / b; // integer divison
14 printf("a / b = %i\n", result);
15
16 result = a + b * c; // priority of the operators
17 printf("a + b * c = %i\n", result);
18
19 printf("a * b + c * d = %i\n", a * b + c * d); // -> 50
20 printf("(a * b) + (c * d) = %i\n", (a * b) + (c * d)); // -> 50
21 printf("a * (b + c) * d = %i\n", a * (b + c) * d); // -> 350

```

*lec01/arithmetic\_operators.c*

### Example – Arithmetic Operators 2/2

```

1 #include <stdio.h>
2
3 int main(void)
4 {
5     int x1 = 1;
6     double y1 = 2.2357;
7     float x2 = 2.5343f;
8     double y2 = 2;
9
10    printf("P1 = (%i, %f)\n", x1, y1);
11    printf("P1 = (%i, %i)\n", x1, (int)y1);
12    printf("P1 = (%f, %f)\n", (double)x1, (double)y1);
13    printf("P1 = (%.3f, %.3f)\n", (double)x1, (double)y1);
14
15    printf("P2 = (%f, %f)\n", x2, y2);
16
17    double dx = (x1 - x2); // implicit data conversion to float
18    double dy = (y1 - y2); // and finally to double
19
20    printf("(P1 - P2)=(%.3f, %0.3f)\n", dx, dy);
21    printf("|P1 - P2|^2=%.2f\n", dx * dx + dy * dy);
22    return 0;
23 }

```

lec01/points.c

### Formatted Output – printf()

- Numeric values can be printed to the standard output using `printf()`  
*man printf or man 3 printf*
- The first argument is the format string that defines how the values are printed
- The conversion specification starts with the character ‘%’
- Text string not starting with % is printed as it is
- Basic format strings to print values of particular types are
 

char	%c
_Bool	%i, %u
int	%i, %x, %o
float	%f, %e, %g, %a
double	%f, %e, %g, %a
- Specification of the number of digits is possible, as well as an alignment to left (right), etc.  
*Further options in homeworks and lab exercises.*

### Standard Input and Output

- An executed program within Operating System (OS) environments has assigned (usually text-oriented) standard input (`stdin`) and output (`stdout`)  
*Programs for MCU without OS does not have them*
- The `stdin` and `stdout` streams can be utilized for communication with a user
- Basic function for text-based input is `getchar()` and for the output `putchar()`  
*Both are defined in the standard C library <stdio.h>*
- For parsing numeric values the `scanf()` function can be utilized
- The function `printf()` provides formatted output, e.g., a number of decimal places  
*They are library functions, not keywords of the C language.*

### Formatted Input – scanf()

- Numeric values from the standard input can be read using the `scanf()` function  
*man scanf or man 3 scanf*
- The argument of the function is a format string  
*Syntax is similar to printf()*
- A memory address of the variable has to be provided to set its value from the `stdin`
- Example of readings integer value and value of the `double` type

```

1 #include <stdio.h>
2
3 int main(void)
4 {
5     int i;
6     double d;
7
8     printf("Enter int value: ");
9     scanf("%i", &i); // operator & returns the address of i
10
11    printf("Enter a double value: ");
12    scanf("%lf", &d);
13    printf("You entered %02i and %0.1f\n", i, d);
14
15    return 0;
16 }

```

lec01/scanf.c

### Example: Program with Output to the stdout 1/2

- Instead of `printf()` we can use `fprintf()` with explicit output stream `stdout`, or alternatively `stderr`; both functions from the `<stdio.h>`

```

1 #include <stdio.h>
2
3 int main(int argc, char **argv) {
4     fprintf(stdout, "My first program in C!\n");
5     fprintf(stdout, "Its name is \"%s\"\n", argv[0]);
6     fprintf(stdout, "Run with %d arguments\n", argc);
7     if (argc > 1) {
8         fprintf(stdout, "The arguments are:\n");
9         for (int i = 1; i < argc; ++i) {
10            fprintf(stdout, "Arg: %d is \"%s\"\n", i, argv[i]);
11        }
12    }
13 }
```

### Example: Program with Output to the stdout 2/2

- Notice, using the header file `<stdio.h>`, several other files are included as well to define types and functions for input and output *Check by, e.g., `clang -E print_args.c`*

```

clang print_args.c -o print_args
./print_args first second
My first program in C!
Its name is "./print_args"
It has been run with 3 arguments
The arguments are:
Arg: 1 is "first"
Arg: 2 is "second"
```

### Extended Variants of the main() Function

- Extended declaration of the `main()` function provides access to the environment variables *For Unix and MS Windows like OS*

```
int main(int argc, char **argv, char **envp) { ... }
```

*The environment variables can be accessed using the function `getenv()` from the standard library `<stdlib.h>`.*

`lec01/main_env.c`

- For Mac OS X, there are further arguments

```
int main(int argc, char **argv, char **envp, char **apple)
{
    ...
}
```

## Part III Part 3 – Assignment HW 01

## HW 01 – Assignment

### Topic: ASCII art

Mandatory: **2 points**; Optional: none; Bonus : none

- **Motivation:** Have a fun with loops and user parametrization of the program
- **Goal:** Acquire experience using loops and inner loops
- **Assignment:** <https://cw.fel.cvut.cz/wiki/courses/b3b36prg/hw/hw01>
  - Read parameters specifying a picture of small house using selected ASCII chars  
[https://en.wikipedia.org/wiki/ASCII\\_art](https://en.wikipedia.org/wiki/ASCII_art)
  - Assesment of the input values
- **Deadline:** 07.03.2020, 23:59:59 PST

*PST – Pacific Standard Time*

## Summary of the Lecture

## Topics Discussed

- Information about the Course
- Introduction to C Programming
  - Program, source codes and compilation of the program
  - Structure of the souce code and writting program
  - Variables and basic types
  - Variables, assignment, and memory
  - Basic Expressions
  - Standard input and output of the program
  - Formating input and output
- **Next: Expressions and Bitwise Operations, Selection Statements and Loops**