

- Introduction Parallel Processing Semaphores Shared Memory Messages
- ## The Role of the Operating System (OS)
- OS provides hardware abstraction layer – encapsulate HW and separate the user from the particular hardware architecture (true/pseudo parallelism).
  - OS is responsible for synchronization of running processes.
  - OS provides user interfaces (system calls):
    - To create and destroy processes.
    - To manage processes and processors.
    - To schedule processors on available processors.
    - To control access to shared memory.
    - Mechanisms for inter-process communication (IPC).
    - Mechanisms for processes synchronization.
- Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 15 / 51

- Introduction Parallel Processing Semaphores Shared Memory Messages
- ## Parallel Processing and Programming Languages
- Regarding parallel processing programming languages can be divided into languages w/o and with explicit support for the parallelism.
    - Without explicit support for parallelism – possible mechanisms of parallel processing.
      - Parallel processing is realized by compiler and operating system.
      - Parallel constructions are explicitly marked for the compiler.
      - Parallel processing is performed by OS system calls.
    - With explicit support for parallelism.
- Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 17 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

## Example of Parallel Processing Realized by Compiler 1/2

### Example – Array Multiplication

```

1 #include <stdlib.h>
2 #define SIZE 30000000
3 int main(int argc, char *argv[])
4 {
5     int i;
6     int *in1 = (int*)malloc(SIZE*sizeof(int));
7     int *in2 = (int*)malloc(SIZE*sizeof(int));
8     int *out = (int*)malloc(SIZE*sizeof(int));
9     for (i = 0; i < SIZE; ++i) {
10        in1[i] = i;
11        in2[i] = 2 * i;
12    }
13    for (i = 0; i < SIZE; ++i) {
14        out[i] = in1[i] * in2[i];
15        out[i] = out[i] - (in1[i] + in2[i]);
16    }
17    return 0;
18 }
19 }

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 18 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

## Example of Parallel Processing Realized by Compiler 2/2

### Example 1

```

1 icc compute.c
2 time ./a.out
3 real 0m0.562s
4 user 0m0.180s
5 sys 0m0.384s

```

### Example 2

```

1 icc -mssse compute.c; time ./a.out
2 compute.c(8) : (col. 2) remark: LOOP WAS VECTORIZED.
3 real 0m0.542s
4 user 0m0.136s
5 sys 0m0.408s

```

### Example 3

```

1 icc -parallel compute.c; time ./a.out
2 compute.c(12) : (col. 2) remark: LOOP WAS AUTO-PARALLELIZED.
3 real 0m0.702s
4 user 0m0.484s
5 sys 0m0.396s

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 19 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

## Example – Open MP – Matrix Multiplication 1/2

- Open Multi-Processing (OpenMP) – application programming interface for multi-platform shared memory multiprocessing. <http://www.openmp.org>
- We can instruct the compiler by macros for parallel constructions.
  - E.g., parallelization over the outside loop for the *i* variable.

```

1 void multiply(int n, int a[n][n], int b[n][n], int c[n][n])
2 {
3     int i;
4     #pragma omp parallel private(i)
5     #pragma omp for schedule (dynamic, 1)
6     for (i = 0; i < n; ++i) {
7         for (int j = 0; j < n; ++j) {
8             c[i][j] = 0;
9             for (int k = 0; k < n; ++k) {
10                c[i][j] += a[i][k] * b[k][j];
11            }
12        }
13    }
14 }

```

lec10/demo-omp-matrix.c  
Squared matrices of the same dimensions are used for simplicity.

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 20 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages


### Example – Open MP – Matrix Multiplication 2/2

- Comparison of matrix multiplication with  $1000 \times 1000$  matrices using OpenMP on iCore5 (2 cores with HT).

```

1 gcc -std=c99 -O2 -o demo-omp demo-omp-matrix.c
2 ./demo-omp 1000
3 Size of matrices 1000 x 1000 naive
4   multiplication with 0(n^3)
5 c1 == c2: 1
6 Multiplication single core 9.33 sec
7 Multiplication multi-core 4.73 sec
8 export OMP_NUM_THREADS=2
9 ./demo-omp 1000
10 Size of matrices 1000 x 1000 naive
11   multiplication with 0(n^3)
12 c1 == c2: 1
13 Multiplication single core 9.48 sec
14 Multiplication multi-core 6.23 sec

```



Use, e.g., `top` program for a list of running processes/threads.

```
lec10/demo-omp-matrix.c
```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 21 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Languages with Explicit Support for Parallelism

- It has support for creation of new processes.
  - Running process create a copy of itself.
    - Both processes execute the identical code (copied).
    - The **parent** process and **child** process are distinguished by the process identifier (PID).
  - The code segment is explicitly linked with the new process.
- Regardless how a new process is created, the most important is the relation to the parent process execution and memory access.
  - Does the parent process stops its execution till the end of the child process?
  - Is the memory shared by the child and parent processes?
- Granularity of the processes – parallelism ranging from the level of the instructions to the parallelism of programs.

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 22 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Parallelism – Statement Level

Example – **parbegin-parend** block

```

parbegin
S1;
S2;
...
Sn;
parend

```

- Statement  $S_1$  are  $S_n$ , executed in parallel.
- Execution of the main program is interrupted until all statements  $S_1$  to  $S_n$  are terminated.
- Statement  $S_1$  are  $S_n$ , executed in parallel.

Example – **doparallel**

```

1 for i = 1 to n doparallel {
2   for j = 1 to n do {
3     c[i,j] = 0;
4     for k = 1 to n do {
5       c[i,j] = c[i,j] + a[i,k]*b[k,j];
6     } }

```

Parallel execution of the outer loop over all  $i$ .

E.g., *OpenMP in C.*

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 23 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Parallelism – Procedure Level

- A procedure is coupled with the execution process.
  - procedure P;
  - `PID`  $x_{pid} = \text{newprocess}(P)$ ;
  - killprocess( $x_{pid}$ );
    - P is a procedure and  $x_{pid}$  is a process identifier.
- Assignment of the procedure/function to the process at the declaration
  - `PID`  $x_{pid}$  process(P).
    - The process is created at the creation of the variable  $x$ .
    - The process is terminated at the end of  $x$  or sooner.

E.g., *Threads (pthreads) in C.*

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 24 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Parallelism – Program (Process) Level

- A new process can be only a whole program.
- A new program is created by a system call, which creates a complete copy of itself including all variable and data at the moment of the call.

Example - Creating a copy of the process by fork system call

```

1 if (fork() == 0) {
2   /* code executed by the child process */
3 } else {
4   /* code executed by the parent process */
5 }

```

E.g., *fork() in C*

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 25 / 51


Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – fork()

```

1 #define NUMPROCS 4
2 for (int i = 0; i < NUMPROCS; ++i) {
3   pid_t pid = fork();
4   if (pid == 0) {
5     compute(i, n);
6     exit(0);
7   } else {
8     printf("Child %d created\n", pid);
9   }
10 }
11 printf("All processes created\n");
12 for (int i = 0; i < NUMPROCS; ++i) {
13   pid_t pid = wait(&r);
14   printf("Wait for pid %d return: %d\n", pid, r);
15 }
16 void compute(int myid, int n)
17 {
18   printf("Process myid %d start computing\n", myid);
19   ...
20   printf("Process myid %d finished\n", myid);
21 }

```



```

clang demo-fork.c && ./a.out
Child 2049 created
Child 2050 created
Process myid 1 start computing
Process myid 2 start computing
Child 2051 created
Child 2052 created
Process myid 3 start computing
All processes created
Process myid 0 finished
Wait for pid 2050 return: 0
Process myid 3 finished
Process myid 2 finished
Wait for pid 2049 return: 0
Wait for pid 2051 return: 0
Wait for pid 2052 return: 0

```

lec10/demo-fork.c

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 26 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Semaphore

- E. W. Dijkstra – semaphore is a mechanism to synchronize parallel processes with shared memory.
- Semaphore is an integer variable with the following operations.
  - InitSem** - initialization.
  - Wait**
    - If  $S > 0$  then  $S \leftarrow S - 1$  (resources are available, in this case, acquire one).
    - Otherwise suspend execution of the calling process (wait for  $S$  become  $S > 0$ ).
  - Signal**
    - If there is a waiting process, awake it (let the process acquire one resource).
    - Otherwise increase value of  $S$  by one, i.e.,  $S \leftarrow S + 1$  (release one resource).
- Semaphores can be used to control access to shared resource.
  - $S < 0$  - shared resource is in use. The process asks for the access to the resources and waits for its release.
  - $S > 0$  - shared resource is available. The process releases the resource.

The value of the semaphore can represent the number of available resources. Then, we can acquire (or wait for)  $k$  resources – `wait(k)`:  $S \leftarrow S - k$  for  $S > k$ , and also releases  $k$  resources – `signal(k)`:  $S \leftarrow S + k$ .

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 28 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Semaphores Implementation

- Operations with a semaphore must be atomic.
  - The processor cannot be interrupted during execution of the operation.
- Machine instruction **TestAndSet** reads and stores a content of the addressed memory space and set the memory to a non-zero value.
- During execution of the **TestAndSet** instructions the processor holds the system bus and access to the memory is not allowed for any other processor.

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 29 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Usage of Semaphores

- Semaphores can be utilized for defining a **critical sections**.
- Critical sections is a part of the program where exclusive access to the shared memory (resources) must be guaranteed.

Example of critical section protected by a semaphore

```

InitSem(S,1);
Wait(S);
/* Code of the critical section */
Signal(S);

```

- Synchronization of the processes using semaphores.

Example of synchronization of processes.

```

/* process p */
InitSem(S,0)
Wait(S); ...
exit();

/* process q */
Signal(S);
exit();

```

Process p waits for termination of the process q.

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 30 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Semaphore 1/4 (System Calls)

- Semaphore is an entity of the Operating System (OS).

```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/sem.h>
4 /* create or get existing set of semaphores */
5 int semget(key_t key, int nsems, int flag);
6 /* atomic array of operations on a set of semaphores */
7 int semop(int semid, struct sembuf *array, size_t nops);
8 /* control operations on a set of semaphores */
9 int semctl(int semid, int semnum, int cmd, ...);

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 31 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Semaphore 2/4 (Synchronization Protocol)

- Example when the main (primary) process waits for two other processes (secondary) become ready.
  - Primary process suspend the execution and waits for two other secondary processes become ready.
  - Secondary processes then wait to be released by the primary process.
- Proposed synchronization "protocol".
  - Define our way to synchronize the processes using the system semaphores.
  - Secondary process increments semaphore by 1.
  - Secondary process waits the semaphore become 0 and then it is terminated.
  - Primary process waits for two secondary processes and decrements the semaphore about 2.
    - It must also ensure the semaphore value is not 0; otherwise secondary processes would be terminated prematurely.
  - We need to use the atomic operations with the semaphore.

```

lec10/sem-primary.c lec10/sem-secondary.c

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 32 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Semaphore 3/4 (Primary Process)

```

1 int main(int argc, char* argv[])
2 {
3     struct sembuf sem[2]; // structure for semaphore atomic operations
4     int id = semget(1000, 1, IPC_CREAT | 0666); // create semaphore
5     if (id != -1) {
6         int r = semctl(id, 0, SETVAL, 0) == 0;
7         sem[0].sem_num = 0; // operation to acquire semaphore
8         sem[0].sem_op = -2; // once its value will be >= 2
9         sem[0].sem_flg = 0; // representing two secondary processes are ready
10        sem[1].sem_num = 0; // the next operation in the atomic set
11        sem[1].sem_op = 2; // of operations increases the value of
12        sem[1].sem_flg = 0; // the semaphore about 2
13        printf("Wait for semvalue >= 2\n");
14        r = semop(id, sem, 2); // perform all operations atomically
15        printf("Press ENTER to set semaphore to 0\n");
16        getchar();
17        r = semctl(id, 0, SETVAL, 0) == 0; // set the value of semaphore
18        r = semctl(id, 0, IPC_RMID, 0) == 0; // remove the semaphore
19    }
20    return 0;
21 }

```

lec10/sem-primary.c

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 33 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Semaphore 4/4 (Secondary Process)

```

1 int main(int argc, char* argv[])
2 {
3     struct sembuf sem;
4     int id = semget(1000, 1, 0);
5     int r;
6     if (id != -1) {
7         sem.sem_num = 0; // add the secondary process
8         sem.sem_op = 1; // to the "pool" of resources
9         sem.sem_flg = 0;
10        printf("Increase semaphore value (add resource)\n");
11        r = semop(id, &sem, 1);
12        sem.sem_op = 0;
13        printf("Semaphore value is %d\n", semctl(id, 0, GETVAL, 0));
14        printf("Wait for semaphore value 0\n");
15        r = semop(id, &sem, 1);
16        printf("Done\n");
17    }
18    return 0;
19 }

```

lec10/sem-secondary.c

- The IPC entities can be listed by `ipcs`.

```

clang sem-primary.c -o sem-primary
clang sem-secondary.c -o sem-secondary

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 34 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Issues with Semaphores

- The main issues are arising from a wrong usage.
- Typical mistakes are as follows.
  - Wrongly identified a critical section.
  - Process may block by multiple calls of `wait(S)`.
  - E.g., the `deadlock` issues may arise from situations like.

#### Example – Deadlock

```

/* process 1*/ /* process 2*/
...           ...
wait(S1);     wait(S2);
wait(S2);     wait(S1);
Signal(S2);   Signal(S1);
Signal(S1);   Signal(S2);
...           ...

```

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 35 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Shared Memory

- Labeled part of the memory accessible from different processes.
- OS service provided by system calls.

#### Example of System Calls

```

1 /* obtain a shared memory identifier */
2 int shmget(key_t key, size_t size, int flag);
3 /* attach shared memory */
4 void* shmat(int shmid, const void *addr, int flag);
5 /* detach shared memory */
6 int shmdt(const void *addr);
7 /* shared memory control */
8 int shmctl(int shmid, int cmd, struct shmids *buf);

```

- OS manages information about usage of shared memory.
- OS also manages permissions and access rights.

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 37 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Shared Memory 1/4 (Write)

- Write a line read from `stdin` to the shared memory.

```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/shm.h>
4 #include <stdio.h>
5 #define SIZE 512
6 int main(int argc, char *argv[])
7 {
8     char *buf;
9     int id;
10    if ((id = shmget(1000, SIZE, IPC_CREAT | 0666)) != -1) {
11        if ((buf = (char*)shmat(id, 0, 0)) != 0) {
12            fgets(buf, SIZE, stdin);
13            shmdt(buf);
14        }
15    }
16    return 0;
17 }

```

lec10/shm-write.c

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 38 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Shared Memory 2/4 (Read)

- Read a line from the shared memory and put it to the `stdout`.

```

1 #include <sys/types.h>
2 #include <sys/shm.h>
3 #include <stdio.h>
4 #define SIZE 512
5 int main(int argc, char *argv[])
6 {
7     int id;
8     char *buf;
9     if ((id = shmget(1000, 512, 0)) != -1) {
10        if ((buf = (char*)shmat(id, 0, 0)) != 0) {
11            printf("mem:%s\n", buf);
12        }
13        shmdt(buf);
14    } else {
15        fprintf(stderr, "Cannot access to shared memory!\n");
16    }
17    return 0;
18 }

```

lec10/shm-read.c

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 39 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Shared Memory 3/4 (Demo)

- Use `shm-write` to write a text string to the shared memory.
- Use `shm-read` to read data (string) from the shared memory.
- Remove shared memory segment.
- Try to read data from the shared memory.

```

ipcrm -M 1000
1 % clang -o shm-write shm-write.c
2 % ./shm-write
3 Hello! I like programming in C!
4 % ./shm-read
5 mem:Hello! I like programming in C!
6 % ipcrm -M 1000
7 % ./shm-read
8 Cannot access to shared memory!

```

lec10/shm-write.c lec10/shm-read.c

Jan Faigl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 40 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Shared Memory 4/4 (Status)

- A list of accesses to the shared memory using `ipcs` command.

```

1 after creating shared memory segment and before writing the text
2 m 65539 1000 --rw-rw-rw- jf jf jf jf 1
3 512 1239 1239 22:18:48 no-entry 22:18:48
4 after writing the text to the shared memory
5 m 65539 1000 --rw-rw-rw- jf jf jf jf 0
6 512 1239 1239 22:18:48 22:19:37 22:18:48
7 after reading the text
8 m 65539 1000 --rw-rw-rw- jf jf jf jf 0
9 512 1239 1260 22:20:07 22:20:07 22:18:48

```

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 41 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Sensing Messages and Queues of Messages

- Processes can communicate via messages send/received to/from system messages queues.
- Queues are entities of the OS with defined system calls.

#### Example of System Calls

```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/msg.h>
4
5 /* Create a new message queue */
6 int msgget(key_t key, int msgflg);
7
8 /* Send a message to the queue -- block/non-block (IPC_NOWAIT) */
9 int msgsnd(int msqid, const void *mmsgp, size_t msgsz, int msgflg);
10
11 /* Receive message from the queue -- block/non-block (IPC_NOWAIT) */
12 int msgrcv(int msqid, void *mmsgp, size_t msgsz, long msgtyp, int msgflg);
13
14 /* Control operations (e.g., destroy) the message queue */
15 int msgctl(int msqid, int cmd, struct msqid_ds *buf);

```

Another message passing system can be implemented by a user library. e.g., using network communication.

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 43 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Messages Passing 1/4 (Synchronization, Primary)

- Two processes are synchronized using messages.
  - The **primary** process waits for the message from the **secondary** process
  - The primary process informs secondary to solve the task.
  - The secondary process informs primary about the solution.
  - The primary process sends message about termination.

#### Example of Master Process 1/2

```

1 struct msgbuf {
2     long mtype;
3     char mtext[SIZE];
4 };
5
6 int main(int argc, char *argv[])
7 {
8     struct msgbuf msg;
9     int id = msgget(KEY, IPC_CREAT | 0666);
10    int r;
11    if (id != -1) {

```

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 44 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Messages Passing 2/4 (Primary)

#### Example of Primary Process 2/2

```

1 msg.mtype = 3; //type must be > 0
2 printf("Wait for other process\n");
3 r = msgrcv(id, &msg, SIZE, 3, 0);
4 printf("Press ENTER to send work\n");
5 getchar();
6 strcpy(msg.mtext, "Do work");
7 msg.mtype = 4; //work msg is type 4
8 r = msgsnd(id, &msg, sizeof(msg.mtext), 0);
9 fprintf(stderr, "msgsnd r:%d\n", r);
10 printf("Wait for receive work results\n", r);
11 msg.mtype = 5;
12 r = msgrcv(id, &msg, sizeof(msg.mtext), 5, 0);
13 printf("Received message:%s\n", msg.mtext);
14 printf("Press ENTER to send exit msg\n");
15 getchar();
16 msg.mtype = EXIT_MSG; //I choose type 10 as exit msg
17 r = msgsnd(id, &msg, 0, 0);
18 }
19 return 0;
20 }

```

lec10/msg-primary.c

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 45 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Messages Passing 3/4 (Secondary)

```

1 int main(int argc, char *argv[])
2 {
3     ...
4     msg.mtype = 3;
5     printf("Inform main process\n");
6     strcpy(msg.mtext, "I'm here, ready to work");
7     r = msgsnd(id, &msg, sizeof(msg.mtext), 0);
8     printf("Wait for work\n");
9     r = msgrcv(id, &msg, sizeof(msg.mtext), 4, 0);
10    printf("Received message:%s\n", msg.mtext);
11    for (i = 0; i < 4; i++) {
12        sleep(1);
13        printf(".");
14        fflush(stdout);
15    } //do something useful
16    printf("Work done, send wait for exit\n");
17    strcpy(msg.mtext, "Work done, wait for exit");
18    msg.mtype = 5;
19    r = msgsnd(id, &msg, sizeof(msg.mtext), 0);
20    msg.mtype = 10;
21    printf("Wait for exit msg\n");
22    r = msgrcv(id, &msg, SIZE, EXIT_MSG, 0);
23    printf("Exit message has been received\n");

```

lec10/msg-secondary.c

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 46 / 51

Introduction Parallel Processing Semaphores Shared Memory Messages

### Example – Messages Passing 4/4 (Demo)

- Execute the primary process.
- Execute the secondary process.
- Perform the computation.
- Remove the created message queue identified by the `msgid`.

```

1 % clang msg-primary.c -o primary
2 % ./primary
3 Wait for other process
4 Worker msg received, press ENTER to send
5 work msg
6 msgsnd r:0
7 Wait for receive work results
8 Received message:I'm going to wait for
9 exit msg
10 Press ENTER to send exit msg
11 % ipcrm -Q 1000
12 % ipcrm -Q 1000
13 ipcrm: msgq(1000): : No such file or
14 % directory

```

```

1 % clang msg-secondary.c -o secondary
2 % ./secondary
3 Inform main process
4 Wait for work
5 Received message:Do work
6 ...done
7 Work done, send wait for exit
8 Wait for exit msg
9 Exit message has been received
10 % ipcs -q
11 Message Queues:
12 T ID KEY MODE OWNER GROUP
13 q 65536 1000 -rw-rw- jf jf
14 %

```

ipcrm -Q 1000

lec10/msg-primary.c lec10/msg-secondary.c

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 47 / 51

Topics Discussed

## Summary of the Lecture

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 48 / 51

Topics Discussed

- Introduction to Parallel Programming
  - Ideas and main architectures
  - Program and process in OS
- Parallel processing
- Synchronization and Inter-Process Communication (IPC)
  - Semaphores
  - Messages
  - Shared memory
- Next: Multithreading programming

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 49 / 51

Pipeline-based communication Parallel Computing using GPU

## Část III

## Appendix

Jan Faijl, 2024 BAB36PRGA – Přednáška 10: Parallel Programming 50 / 51

### Signal Generator and Visualization

- Let us have a signal generator `sgen`, which is a program that generate a sequence of values to its `stdout`.
- The visualization can be realized in another application `tsgnal_viewer` that reads signal values from the `stdin`.
- We can connect these two applications by `./sgen | ./tsgnal_viewer`.

```

$ ./sgen          $ ./sgen | wc
0.000000          65772  65772  618529
1.075095
1.031029
0.818540
0.748307
0.549199
0.342997
-0.149521
-0.016643
-0.147374
-0.239563
-0.293963
-0.314364
-0.306833
-0.279048
-0.239311
-0.196373

```



HW9B is an extension of the concept using user defined communication protocol between a signal generator and control application with visualization and multi-threading programming.

### Massive parallelism using graphics cards

- Image rendering performed pixel-by-pixel can be easily parallelized.
- Graphics Processing Units (GPU) has similar (or even higher) degree of integration with the main processors (CPU).
- They have huge number of parallel processors. *E.g., GeForce GTX 1060 ~ 1280 cores.*
- The computational power can also be used in another applications.
  - Processing stream of data (SIMD instructions - processors).
  - GPGPU - General Purpose computation on GPU. <http://www.gpgpu.org>
  - OpenCL (Open Computing Language) – GPGPU abstract interface.
  - CUDA - Parallel programming interface for NVIDIA graphics cards. [http://www.nvidia.com/object/cuda\\_home.html](http://www.nvidia.com/object/cuda_home.html)

### Computational Power (2008)

- What is the reported processor computational power?
- Graphics (stream) processors.
 

CSX700	96 GigaFLOPs
Cell	102 GigaFLOPs
GeForce 8800 GTX	518 GigaFLOPs
Radeon HD 4670	480 GigaFLOPs

*Peak catalogue values.*
- Main processors :
 

Phenom X4 9950 (@2.6 GHz)	21 GigaFLOPs
Core 2 Duo E8600 (@3.3 GHz)	22 GigaFLOPs
Cure 2 Quad QX9650 (@3.3 GHz)	35 GigaFLOPs
Core 2 Quad QX9650 (@3.3 GHz)	35 GigaFLOPs
Core i7 970 (@3.2 GHz)	42 GigaFLOPs

*Test linpack 32-bit.*
- Is the reported power really achievable? *(float vs double)*
- How about other indicators? *E.g., computational power / power consumption.*
  - CSX700 has typical power consumption around 9W.

### CUDA



- NVIDIA Compute Unified Device Architecture.
- Extension of the C to access to the parallel computational units of the GPU.
- Computation (**kernel**) is executed by the GPU.
- Kernel is performed in parallel using available computational units.
- Host** - Main processor (process).
- Device** - GPU.
- Data must be in the memory accessible by the GPU.
  - Host memory → Device memory
- The result (of the computation) is stored in the GPU memory.
  - Host memory ← Device memory

### CUDA – Computational Model

- Kernel (computation) is divided into blocks.
- Each block represent a parallel computation of the part of the result. *E.g., a part of the matrix multiplication.*
- Each block consists of computational threads.
- Parallel computations are synchronization within the block.
- Blocks are organized into the **grid**.
- Scalability is realized by dividing the computation into blocks.
 

*Blocks may not be necessarily computed in parallel. Based on the available number of parallel units, particular blocks can be computed sequentially.*

### CUDA – Grid, Blocks, Threads, and Memory Access



- Access time to the memory.
- Collisions for simultaneous access of several threads.

### CUDA – Example – Matrix Multiplication 1/8

- NVIDIA CUDA SDK - Version 2.0, `matrixMul`.
- Simple matrix multiplication.
  - $C = A \cdot B$ ,
  - Matrices have identical dimensions  $n \times n$ ,
  - where  $n$  is the multiple of the block size.
- Comparison
  - naive implementation in C (3x for loop),
  - naive implementation in C with matrix transpose.
  - CUDA implementation.
- Hardware
  - CPU - Intel Core 2 Duo @ 3 GHz, 4 GB RAM,
  - GPU - NVIDIA G84 (GeForce 8600 GT), 512 MB RAM.

### CUDA – Example – Matrix Multiplication 2/8

```

Naive implementation
1 void simple_multiply(const int n,
2   const float *A, const float *B, float *C)
3 {
4   for (int i = 0; i < n; ++i) {
5     for (int j = 0; j < n; ++j) {
6       float prod = 0;
7       for (int k = 0; k < n; ++k) {
8         prod += A[i * n + k] * B[k * n + j];
9       }
10      C[i * n + j] = prod;
11    }
12  }
13 }

```

### CUDA – Example – Matrix Multiplication 3/8


```

Naive implementation with transpose
1 void simple_multiply_trans(const int n,
2   const float *a, const float *b, float *c)
3 {
4   float * bT = create_matrix(n);
5   for (int i = 0; i < n; ++i) {
6     bT[i*n + i] = b[i*n + i];
7     for (int j = i + 1; j < n; ++j) {
8       bT[i*n + j] = b[j*n + i];
9       bT[j*n + i] = b[i*n + j];
10    }
11  }
12  for (int i = 0; i < n; ++i) {
13    for (int j = 0; j < n; ++j) {
14      float tmp = 0;
15      for (int k = 0; k < n; ++k) {
16        tmp += a[i*n + k] * bT[j*n + k];
17      }
18      c[i*n + j] = tmp;
19    }
20  }
21  free(bT);
22 }

```

### CUDA – Example – Matrix Multiplication 4/8

- CUDA – computation strategy
  - Divide matrices into blocks.
  - Each block computes a single sub-matrix  $C_{sub}$ .
  - Each thread of the individual blocks computes a single element of  $C_{sub}$ .



### CUDA – Example – Matrix Multiplication 5/8

```

CUDA – Implementation – main function
1 void cuda_multiply(const int n,
2   const float *hostA, const float *hostB, float *hostC)
3 {
4   const int size = n * n * sizeof(float);
5   float *devA, *devB, *devC;
6   cudaMalloc((void**)&devA, size);
7   cudaMalloc((void**)&devB, size);
8   cudaMalloc((void**)&devC, size);
9
10  cudaMemcpy(devA, hostA, size, cudaMemcpyHostToDevice);
11  cudaMemcpy(devB, hostB, size, cudaMemcpyHostToDevice);
12
13  dim3 threads(BLOCK_SIZE, BLOCK_SIZE); // BLOCK_SIZE == 16
14  dim3 grid(n / threads.x, n / threads.y);
15
16  // Call kernel function matrixMul
17  matrixMul<<grid, threads>>(n, devA, devB, devC);
18
19  cudaMemcpy(hostC, devC, size, cudaMemcpyDeviceToHost);
20
21  cudaFree(devA);
22  cudaFree(devB);
23  cudaFree(devC);
24
25 }
    
```

### CUDA – Example – Matrix Multiplication 6/8

```

CUDA implementation – kernel function
1 __global__ void matrixMul(int n, float* A, float* B, float* C) {
2   int bx = blockIdx.x; int by = blockIdx.y;
3   int tx = threadIdx.x; int ty = threadIdx.y;
4   int aBegin = n * BLOCK_SIZE * by; //beginning of sub-matrix in the block
5   int aEnd = aBegin + n - 1; //end of sub-matrix in the block
6   float Csub = 0;
7   for (
8     int a = aBegin, b = BLOCK_SIZE * bx;
9     a <= aEnd;
10    a += BLOCK_SIZE, b += BLOCK_SIZE * n
11   ) {
12     __shared__ float As[BLOCK_SIZE][BLOCK_SIZE]; // shared memory within
13     __shared__ float Bs[BLOCK_SIZE][BLOCK_SIZE]; // the block
14     As[ty][tx] = A[a + n * ty + tx]; // each thread reads a single element
15     Bs[ty][tx] = B[b + n * ty + tx]; // of the matrix to the memory
16     __syncthreads(); // synchronization, sub-matrix in the shared memory
17     for (int k = 0; k < BLOCK_SIZE; ++k) { // each thread computes
18       Csub += As[ty][k] * Bs[k][tx]; // the element in the sub-matrix
19     }
20   }
21   __syncthreads();
22 }
23 int c = n * BLOCK_SIZE * by + BLOCK_SIZE * bx;
24 C[c + n * ty + tx] = Csub; // write the results to memory
25 }
    
```

### CUDA – Example – Matrix Multiplication 7/8

- CUDA source codes.
- Example – Dedicated source file `cuda_func.cu`
- 1. Declaration of the external function.
 

```

extern "C" { // declaration of the external function (cuda kernel)
void cuda_multiply(const int n, const float *A, const float *B, float *C);
}
            
```
- 2. Compile the CUDA code to the C++ code.
 

```

1 nvcc --cuda cuda_func.cu -o cuda_func.cu.cc
            
```
- 3. Compilation of the `cuda_func.cu.cc` file using standard compiler.

### CUDA – Example – Matrix Multiplication 8/8

